

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:











[Molex Connector Corporation](#)
[0463965231](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

PART NUMBER	NUMBER OF WIRE OPENINGS	CIRCUIT POSITION	WIRE SIZE(S) SEE NOTE 6	WIRE HOLE DIAMETER
46396-5201	3	1, 2, 3	16 AWG	2.34/.092
46396-5202	2	4, 5	10 AWG	4.46/.176
46396-5203	3	3, 4, 5	16 AWG	2.74/.108
46396-5204	3	1, 2, 3	12 AWG	3.92/.154
46396-5205	3	1, 2, 3	10 AND 12 AWG	2.4/.102 (2.4/.102) (3.2/.125)
46396-5211	3	1, 2, 3	16 AWG	2.74/.108
46396-5231	5	1, 2, 3, 4, 5	12 AWG	4.00/.158

- NOTES:
1. MATERIAL: PBT OR EQUIVALENT, 94V-0, COLOR: BLACK
 2. HOUSING ACCEPTS MOLEX TERMINAL SERIES: 44262-4**** (SEE MOLEX DRAWING NUMBER SD-44262-001 FOR TERMINAL OPTIONS)
 3. HOUSING AND ASSOCIATED COMPONENTS ARE RoHS COMPLIANT
 4. PACKAGED PER MOLEX PACKAGING SPEC: PK-46396-****
 5. RECEPTACLE HOUSING MATES WITH PLUG HOUSING 46394-5001 (SEE MOLEX DRAWING NUMBER SD-46394-001 FOR DETAILS)
 6. FINAL FIT OF WIRE THRU WIRE OPENINGS WILL DEPEND ON THE OUTSIDE DIAMETER OF THE WIRE.



WIRE OPENING CONFIGURATIONS
CONNECTORS SHOWN CLOSED

ADD PART NOS. TO CH EC NO. UEP2005-0623 (T) DRAWING DATA 2008/07/25 CHKC: 2008/07/25 APPROVAL: (S) 2008/07/25 REV:	QUALITY SYMBOLS	GENERAL TOLERANCES (UNLESS SPECIFIED)	DIMENSION STYLE	SCALE	DESIGN UNITS	THIRD ANGLE PROJECTION	
	∇ -0 ∇ -0 ∇ -0	mm INCH	4 PLACES ±.005 3 PLACES ±.005 2 PLACES ±0.13 ±.010 1 PLACE ±0.25 ±.010 ANGULAR ±1/2°	MM/IN	2:1	METRIC	
	DRAWN BY CHECKED BY APPROVED BY	DATE DATE DATE	MDATA 07-10-07 MDATA 2007/01/15 MDATA 2007/01/15				RECEPTACLE HOUSING 5 POSITION WITH LATCH POWER CONNECTOR
	MATERIAL NO. SEE CHART	DOCUMENT NO. SD-46396-101	MOLEX MOLEX INCORPORATED				SHEET NO. 1 OF 1