

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:


[HellermannTyton](#)
[109-00136](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

HellermannTyton

109-00136



Article Number: 109-00136

Q Tie, 11.4" Long, 50lb Tensile Strength, PA66HS, Natural, 100/pkg



Download drawing



Download spec sheet

Base Data

Local Order Number 109-00136

Type Q50I

Color Natural (NA)

- Features and Benefits**
- Open-head design with easily detectable slot opening allows for swift and easy insertion
 - Pre-lock feature allows for a temporary hold
 - The large ribbed tail permits an ergonomic installation
 - Two rails on the strap ensure guidance through the cable tie head

Product Description Q Ties have a distinctive open-style head, a pre-lock function, and a large ribbed tail. The easily detectable slot opening offered with the tail and tie head offers ease of placement especially when working with gloves is necessary or for blind applications with limited view of the installation. The pre-lock feature allows for temporary holding of cable and wire bundles, permitting additional cables and wires to be placed without destroying the cable tie. Q Ties can be tensioned by hand or with one of HellermannTyton's mechanical cable tie application tools.

Short Description Q Tie, 11.4" Long, 50lb Tensile Strength, PA66HS, Natural, 100/pkg

Product Dimensions

Minimum Tensile Strength (Imperial) 50.0 lbs

Minimum Tensile Strength (Metric) 220 N

Length L (Imperial) 11.4 "

Length L (Metric) 290 mm

Fixation Method None

Identification Plate Position none

Releasable Closure No

Tie Closure plastic pawl

Variant Inside Serrated

Width W (Imperial) 0.19 "

Width W (Metric) 4.7 mm

Bundle Diameter Min. (Imperial) 0.12 "

Bundle Diameter Max. (Imperial) 3.0 "

Bundle Diameter Max. (Metric) 75.0 mm

Thickness T (Imperial) 0.06 "

Thickness T (Metric) 1.5 mm

Logistics and Packaging

Quantity Per bag

Material and Specifications

Material	Polyamide 6.6 heat stabilized (PA66HS)
Material Shortcut	PA66HS
Flammability	UL94 V2
Halogenfree	Yes
Operating Temperature	-40°F to +221°F (-40°C to +105°C)
ROHS Compliant	Yes
Certification/Specification	UL62275