

## Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)  
[151-10916](#)

For any questions, you can email us directly:  
[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)

# HellermannTyton

151-10916

**Article Number: 151-10916**

**Q Mount with Adhesive, 1.6" x 1.6" x 0.26", 4 way entry for Q18 thru Q120 ties, PA66, Black, 100/bag**



Download drawing



Download spec sheet

## Base Data

**Local Order Number** 151-10916

**Type** QM40A

**Color** Black (BK)

**Features and Benefits** • 2- or 4-way entry options for the Q Tie, offering flexibility and stability

**Product Description** Q Mounts are designed to work exclusively with the Q Tie cable tie series. This mounting component is available with adhesive or can be secured with screws. The Q Mount allows either a 2- or 4-way entry for the Q Tie, providing a quick and simple insertion into the mount. Once in place, the Q Tie will not slip out, even in vertical mounting applications.

**Short Description** Q Mount with Adhesive, 1.6" x 1.6" x 0.26", 4 way entry for Q18 thru Q120 ties, PA66, Black, 100/bag

## Product Dimensions

**Length L (Imperial)** 1.6 "

**Length L (Metric)** 40.0 mm

**Fixation Method** Screw Mounting and Adhesive

**Width W (Imperial)** 1.6 "

**Width W (Metric)** 40.0 mm

**Cable Tie Width Max. (Imperial)** 0.31 "

**Cable Tie Width Max. (Metric)** 8.4 mm

**Height H (Imperial)** 0.26 "

**Height H (Metric)** 5.5 mm

**Mounting Hole Diameter D (Imperial)** 0.16 "

**Mounting Hole Diameter D (Metric)** 4.1 mm

**Mounting Hole Diameter D Min. (Imperial)** 0.16 "

**Mounting Hole Centers (Imperial)** 1.19 "

**Mounting Hole Diameter D Max. (Metric)** 4.1 mm

**Mounting Hole Diameter D Min. (Metric)** 4.1 mm

## Logistics and Packaging

**Quantity Per** bag

**Package Quantity (Metric)** 50 Pieces

## Material and Specifications

**Material** Polyamide 6.6 (PA66)

**Adhesive Shortcut** Synthetic rubber T60

**Adhesive** Synthetic rubber with base of polyethylene foam

**Adhesive Operating Temperature** -40°F to +140°F (-40°C to +60°C)

**Flammability** UL94 V2 (excluding adhesive)

**Halogenfree** Yes

**Operating Temperature** -40°F to +185°F (-40°C to +85°C)

**ROHS Compliant** Yes