

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)
[170-03175](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

HellermannTyton

170-03175



Article Number: 170-03175

Aluminum Laminated Fiberglass Sleeve, 0.38" Dia., Silver, 100.0 ft/Standard Reel



Download drawing



Download spec sheet



Download tech sheet

Base Data

Local Order Number 170-03175

Type BSHTTST38SR

Color Silver (SR)

Features and Benefits

- A layer of aluminum provides protection from chemicals, scraping, cuts and abrasion.
- Additional layer also provides insulation barrier for vulnerable wires and cables within high temperature environments.
- Cuts with ordinary scissors for fast, easy application.

Product Description A tubular shaped sleeving product that combines the protection of bonded aluminum and fiberglass into a single solution that is able to deflect radiant heat away from sensitive components inside the tube.

Short Description Aluminum Laminated Fiberglass Sleeve, 0.38" Dia., Silver, 100.0 ft/Standard Reel

Product Dimensions

Length L (Imperial) 100.0 ft

Length L (Metric) 30.48 m

Reel Length (imperial) 100.0 ft

Bundle Diameter Max. (Imperial) 0.437 "

Bundle Diameter Max. (Metric) 11.1 mm

Diameter D (imperial) 0.38 "

Diameter D (metric) 9.7 mm

Nominal Diameter (Imperial) 3/8 "

Nominal Diameter (Metric) 9.7 mm

Logistics and Packaging

Quantity Per reel

Package Quantity 100 ft

Package Quantity (Metric) 1

Reel Weight (Metric) 1.02 kg

Reel Weight (Imperial) 2.25 lbs

Material and Specifications

Material Glass Fiber (GF)
Aluminium (AL)

Flammability non flammable

Operating Temperature -76°F to +491°F (-60°C to +255°C)



Distributor of HellermannTyton: Excellent Integrated System Limited

Datasheet of 170-03175 - BSHTTST38SR 0.38 SILVER

Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com

ROHS Compliant Yes