

Excellent Integrated System Limited

Stocking Distributor


Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)
[170-20600](#)

For any questions, you can email us directly:
sales@integrated-circuit.com

HellermannTyton

170-20600



Article Number: 170-20600

Helagaine Braided Sleeving, 6.0 mm Dia, Polyamide 6.6, Gray, 328.0 ft/Reel



Download drawing



Download spec sheet

Base Data

Local Order Number 170-20600

Type HEGPA6606

Color Gray (GY)

Features and Benefits

- Nylon monofilament construction weave offers a tight braid that provides full coverage but will not rot or retain moisture.
- Material performs well in wet applications and where abiding substrate has a smooth surface.

Product Description Helagaine Nylon Polyamide Expandable Braided Sleeving is a pliable yet durable sleeve that protects against cuts, abrasion and excessive wear caused by repetitive motion.

Short Description Helagaine Braided Sleeving, 6.0 mm Dia, Polyamide 6.6, Gray, 328.0 ft/Reel

Product Dimensions

Length L (Imperial) 328.0 ft

Length L (Metric) 100.0 m

Reel Length (imperial) 328.0 ft

Bundle Diameter Min. (Imperial) 0.16 "

Bundle Diameter Min. (Metric) 4 mm

Bundle Diameter Max. (Imperial) 0.32 "

Bundle Diameter Max. (Metric) 8 mm

Nominal Diameter (Imperial) 1/4 "

Nominal Diameter (Metric) 6 mm

Braid Density n. 85%

Logistics and Packaging

Quantity Per metre

Package Quantity (Metric) 100 m

Weight (imperial) 1.3 lbs

Weight (Metric) 0.59 kg

Material and Specifications

Material Polyamide 6.6 (PA66)

Material Shortcut PA66

Flammability FMVSS 302
UL94 V2

Halogenfree Yes



Distributor of HellermannTyton: Excellent Integrated System Limited

Datasheet of 170-20600 - HEGPA6606 GRAY BRAIDED SLEEVE

Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com

Operating Temperature -76°F to +302°F (-60°C to +150°C)

ROHS Compliant Yes

Certification/Specification EN 45545: 2013