

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

HellermannTyton 181-00521

For any questions, you can email us directly: <u>sales@integrated-circuit.com</u>



HellermannTyton

181-00521

101-00521		
Α	rticle Number: 181-00521	
s	Solid Wall Wiring Duct, 4" X 4", Adhesive, PVC, White, 120ft/Carton	
	RoHS	
Download drawing	d spec sheet	
Base Data		
Local Order Number	181-00521	
Туре	SDA4X4	
Color	White (WH)	
Features and Benefits	 A temporary film is applied to the covers to protect against scratches and is writable for identification during installation. Cover is flush with the side of the duct for increased wire capacity and allows for tight, side by side duct placemer Covers are provided with a non-slip lining, which insures the covers remain in place during vibration, yet they easily snap on and off. (Covers to be purchased separately) 	
Product Description	HellermannTyton's Pro-Duct, Solid Wall wiring duct efficiently routes and protects wire and cable. Solid Wall wiring duct it designed for straight wire runs where break outs are not required. Pro-Duct, Solid Wall wiring duct is manufactured from high impact, rigid PVC, comes in standard colors of white, gray and black, and is available in 6 foot lengths.	
Short Description	Solid Wall Wiring Duct, 4" X 4", Adhesive, PVC, White, 120ft/Carton	
Product Dimensions		
Length L (Imperial)		
Length L (Metric)		
Width W (Imperial)		
Width W (Metric)		
Width W2 (Imperial)		
Width W2 (Metric)		
Width W6 (imperial)		
Width W6 (metric)		
Height H (Imperial)		
Height H (Metric)		
Mounting Hole Centers (Imperial)	4.0 "	
Logistics and Packaging		
Quantity Per	carton	
Package Quantity	120.0 ft	
Package Quantity (Metric)	36.6 m	
Carton Quantity	420.0.8	

Material and Specifications

Matorial	Polyvinylchloride	

Carton Quantity 120.0 ft



Material Shortcut	PVC
Flammability	self-extinguishing
Operating Temperature	+122°F (+50°C)
ROHS Compliant	Yes
Certification/Specification	CSA UL
UL Listed (US and Canada)	No
UL Recognized (US)	Yes
UL Recognized (US and Canada)	No

© HellermannTyton 2015