

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)

[596-00622](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

HellermannTyton

596-00622

Article Number: 596-00622

Pre-Printed Header Label, WARNING, 3" X 2", PET, Orange, 250/RL



Download spec sheet

Base Data

Local Order Number 596-00622

Type 3X2WARNING

Color Orange (OG)

- Features and Benefits**
- Made with UV stable inks and materials for durability and weather resistance
 - Polyester is resistant to chemicals and solvents and will remain legible in dirty environments.
 - High abrasion and scuff resistance for high performance labeling.
 - Meets NEC & IFC standards for printed text, character height, color and outdoor UV stability to pass inspections

Product Description HellermannTyton pre-printed Solar Installation labels are designed to meet the requirements of the National Electrical Code and the International Fire Code as well as being acceptable to the Authority Having Jurisdiction (AHJ). Labels are made with durable UV stable materials and adhesives that are designed to stick to both baked enamel and powder coat surfaces. Where applicable, labels are made using reflective materials for first responder safety. Some pre-printed labels are printable using a thermal transfer printer when variable voltage or series data must be printed and displayed.

Short Description Pre-Printed Header Label, WARNING, 3" X 2", PET, Orange, 250/RL

Product Dimensions

Length L (Imperial) 2.0 "

Length L (Metric) 50.8 mm

Width W (Imperial) 3.0 "

Width W (Metric) 76.2 mm

Height H (Imperial) 2.0 "

Height H (Metric) 50.8 mm

Logistics and Packaging

Quantity Per reel

Package Quantity 250

Package Quantity (Metric) 250

Labels per Column 1

Labels per Row 1

Weight (imperial) 3.2 oz

Material and Specifications

Material Polyester (PET)

Material Shortcut PET

Adhesive Acrylic



Adhesive Operating Temperature -40°F to +302°F (-40°C to +150°C)

Halogenfree Yes

Operating Temperature -40°F to +302°F (-40°C to +150°C)

ROHS Compliant Yes

UL Recognized (US) Yes