

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

<u>Desco</u> <u>13400</u>

For any questions, you can email us directly: <u>sales@integrated-circuit.com</u>



	STATSHIELD® METAL-IN BOXED SERIES				
Opening Overall width (Ov)	Specifications: Standard Document ANSI/ESD S541 (ANSI/ESD S20.20) ANSI/ESD S11.4		ESD Protect	uirements of: ctive Packaging chnical Requirements	()
	Electrical Properties Surface Resistance:	Typical Values	Test Proce	dures/Method	
ATTENTION STATSHIELD® Contents ESD Shielding Bag Static Metal In Construction Precaution Required Executivatives.com	Outer Surface Inner Surface Discharge Shielding Charge Generation Capacitance Probe (to dissipate 1 KV)	$\begin{array}{l} 1 \times 10^4 \mbox{ to } < 1 \times 10^{11} \mbox{ ohms} \\ 1 \times 10^4 \mbox{ to } < 1 \times 10^{11} \mbox{ ohms} \\ < 20 \mbox{ nJ} \\ Teflon: 0.09 \mbox{ nC/sq. in.} \\ quartz: 0.01 \mbox{ nC/sq. in.} \\ < 30 \mbox{ volts} \end{array}$	Modified Inc Modified Inc	STM11.11 ITM11.31, EIA 541 cline Plane	harge
Length (L) Matter in America Matter in America Lead-free RoHS compliant Bag	Physical Properties Film Thickness Width (Inside Dimensions) Length (Inside Dimensions) Light Transmission	Nominal 0.0030" (0.0762mm) ±10% Nominal -0" / + 0.125" Nominal ± 0.125" >40% (Tobias)	MIL-STD-30		
Date & Lot Code Printed for QC Traceability	Heat Seal Tensile Strength Puncture Resistance Non-corrosive Silicone	>10 lbs/in 4600 PSI, 32 MPa >10 lbs Pass Not detected	375°F, 1/2 s ASTM 882 MIL-STD-30 MIL-STD-30 ASTM E168	5°F, 1/2 sec 60 psi STM 882 IL-STD-3010, 2065 IL-STD-3010, M3005 STM E168	
Weld Seal Width (W) Weld Side Weld Seals 3/8 in. (±0.10)	Marking Adhesion Pass IPC-TM-650 2.4.1 Chemical Properties No effect on aluminum, copper, silver, Sn-Pb coated foil, stainless steel, low carbon steel				
Low Charging Static Dissipative Proprietary Outer Polyester Layer Aluminum Shielding Layer Aluminum Shielding Layer					
Low Charging Static Dissipative Proprietary Inner Polyethylene Layer	RoHS 2, REACH and Conflict Minerals Statement None of the RoHS 2 restricted materials, REACH substances of very high concern as of 2015/12/17, or Conflict Minerals are intentionally added in manufacturing this product. Ref: European Union Directive 2011/65/EU and Regulation (EC) No. 1907/2006/CE. See Desco Industries Inc. Limited Warranty at Desco.com.				
					Made in the
Statshield® bags are packaged 100 per package in an oversized shielding bag.					
See Shielding Bag Storage at TB-7057. STATSHIELD® METAL-IN BOXED, 0.0030" (0.0762mm)					
DESCO	DESCO WEST: 3651 WALNUT AVE PHONE (909) 627-8178 DESCO EAST: ONE COLGATE WA PHONE (781) 821-8370	., CHINO, CA 91710 WEB SITE: <u>Desco.co</u> Y, CANTON, MA 02021-1407	m	DRAWING NUMBER 13330	DATE: June 2016

© 2016 DESCO INDUSTRIES INC. Employee Owned