Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

Easy Braid Co. ET75DT005


For any questions, you can email us directly: sales@integrated-circuit.com





ET75DT005 Datasheet

Technical Specifications



ET75DT005

Desolder Tip - Inner Diameter 1.35mm (0.05")

Tip Style: Desolder
Tip Width: 1.35mm (0.05")

Tip Length: 14.00mm (0.55")


750 Type Cartridge¹: 350°C - 398°C

RoHS Compliant² / Lead Free: YES

For Use With: EB-5000S-1, EB-5000S-2

Material Composition







¹ Easy Braid Co. tip cartridges will typically idle within a temperature range of +/-1.1°C. However, there is variation in idle temperature across tip geometries within an individual temperature series. Easy Braid Co. offers a wide variety of tip geometries from 0.25mm fine point tip to 5mm chisel. The length and geometry of a tip will have an influence on the tip idle temperature. To accurately measure idle temperature it will depend greatly on the measurement method, technique and equipment used. Two different methods or the use of alternative equipment will produce different test results.

Copyright © 2010-2014 Easy Braid Co. All Rights Reserved

 $^{2 \}hspace{1mm} \mbox{Please refer to} \hspace{1mm} \frac{\mbox{http://www.rohs.gov.uk}}{\mbox{for details on RoHS Compliance.}}$