# Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

Easy Braid Co.
ETM70CS152

For any questions, you can email us directly:
sales@integrated-circuit.com

EasyBraid Co.

# ETM70CS152 Datasheet

## Technical Specifications




**ETM70CS152**

***Conical Sharp 0.4mm (0.016")***

| | |
|---|---|
| Tip Style: | Conical Sharp |
| Tip Width: | 0.40mm (0.016") |
| Tip Length: | 8.50mm (0.33") |

| | |
|---|---|
| 70 Type Cartridge[1]: | 350°C - 398°C |
| RoHS Compliant[2] / Lead Free: | YES |
| For Use With: | EB-5000S-1, EB-5000S-2 |

## Material Composition




RoHS Compliant

***All components are RoHS compliant and Lead-Free.***

1 Easy Braid Co. tip cartridges will typically idle within a temperature range of +/-1.1°C. However, there is variation in idle temperature across tip geometries within an individual temperature series. Easy Braid Co. offers a wide variety of tip geometries from 0.25mm fine point tip to 5mm chisel. The length and geometry of a tip will have an influence on the tip idle temperature. To accurately measure idle temperature it will depend greatly on the measurement method, technique and equipment used. Two different methods or the use of alternative equipment will produce different test results.

2 Please refer to http://www.rohs.gov.uk for details on RoHS Compliance.

Copyright © 2010-2012 Easy Braid Co. All Rights Reserved