

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Easy Braid Co.](#)
[ETM80DS526](#)


For any questions, you can email us directly:

sales@integrated-circuit.com

EasyBraid Co.

ETM80DS526 Datasheet

Technical Specifications



ETM80DS526

Knife 4.83mm (0.19"), Increased Tin Area 5.84mm (0.23")

Tip Style: Knife

Tip Width: 4.83mm (0.19")

Tip Length: 16.00mm (0.63")

80 Type Cartridge¹:

420°C - 475°C

RoHS Compliant² / Lead Free:

YES

For Use With:

EB-5000S-1, EB-5000S-2


Material Composition

Gold Plated Connector



Stainless Steel Shaft

Lead-Free Tip



All components are RoHS compliant and Lead-Free.

¹ Easy Braid Co. tip cartridges will typically idle within a temperature range of +/- 1.1°C. However, there is variation in idle temperature across tip geometries within an individual temperature series. Easy Braid Co. offers a wide variety of tip geometries from 0.25mm fine point tip to 5mm chisel. The length and geometry of a tip will have an influence on the tip idle temperature. To accurately measure idle temperature it will depend greatly on the measurement method, technique and equipment used. Two different methods or the use of alternative equipment will produce different test results.

² Please refer to <http://www.rohs.gov.uk> for details on RoHS Compliance.