

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Easy Braid Co.](#)
[ETM80LR403](#)


For any questions, you can email us directly:

sales@integrated-circuit.com



ETM80LR403 Datasheet

Technical Specifications



ETM80LR403

Chisel 60° Long Reach 1.78mm (0.07")

Tip Style: Chisel 60°

Tip Width: 1.78mm (0.07")

Tip Length: 15.00mm (0.59")

80 Type Cartridge¹:

420°C - 475°C

RoHS Compliant² / Lead Free:

YES

For Use With:


EB-5000S-1, EB-5000S-2

Material Composition

Gold Plated Connector

Stainless Steel Shaft

Lead-Free Tip



All components are RoHS compliant and Lead-Free.

¹ Easy Braid Co. tip cartridges will typically idle within a temperature range of +/- 1.1°C. However, there is variation in idle temperature across tip geometries within an individual temperature series. Easy Braid Co. offers a wide variety of tip geometries from 0.25mm fine point tip to 5mm chisel. The length and geometry of a tip will have an influence on the tip idle temperature. To accurately measure idle temperature it will depend greatly on the measurement method, technique and equipment used. Two different methods or the use of alternative equipment will produce different test results.

² Please refer to <http://www.rohs.gov.uk> for details on RoHS Compliance.