

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Panduit](#)

[LCCX4-38BF-L](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.




Material	High Conductivity Seamless Copper Tube
Plating	Electro-Tin
Wire Size	4 STR/FLEX
Wire Type	Stranded Copper: Class B & C Compact, Class G, H, I, K, M, Sizes 3, 4 & 5 Locomotive
Wire Strip Length	1-1/8 in.
Stud Size	3/8 in.
UL Listed Wire Connector	Yes, for applications up to 35kv. Consult cable manufacturer for voltage stress relief instructions with applications greater than 2000 volts.
UL Temperature Rating	90° C
C.S.A Certified Wire Connector	Yes
Panduit Color Code on Barrel	GRAY
Panduit Die Index No. on Barrel	P29
Alternate Industry Die Index No. () on Barrel	(8)



CERTIFIED

LISTED

LISTED
Wire Connector



							 CORP. TINLEY PARK, ILLINOIS		
							LC CX4-38BF-L Copper Lug - Two-Hole, Long Flex Barrel with Window, 90° Angle Tongue		
03	1/05	JHNU	TLC	O	PANDUIT REPLACED WIRE RANGE ON BARREL MARKING	12412			
REV	DATE	BY	CHK	DESCRIPTION			ECN	SCALE	DRAWING NO / CAD FILE
								N/A	LC CX4-38BF-CUST