

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Panduit](#)

[PV14-56RX-L](#)

For any questions, you can email us directly:


sales@integrated-circuit.com



Ring Terminal, Vinyl Expanded Insulation

- Expanded wire entry designed to accommodate wire with a larger insulation thickness
- Ring tongue design assures a secure connection in high vibration applications
- Insulation support helps to prevent wire damage in bending applications
- Brazed seam protects terminal barrel from splitting during the crimp process

- Internal barrel serrations assure good wire contact and maximum tensile strength
- UL Flammability UL 94V-0, maximum insulation temperature 221°F (105°C)
- UL and CSA rated up to 600 V per UL 486A/B



Part Number	Wire Range		Color Code	Max. Ins. Dia.		Stud Size		Length		Width		Clearance		Panduit Crimping Tool	Std. Pkg. Qty.	Std. Ctn. Qty.
	AWG	mm ²		In.	mm	In.	mm	In.	mm	In.	mm	In.	mm			
PV14-8RX-C	16 – 14 AWG	1.5 – 2.5	Blue	0.200	5.1	#8	M4	0.96	24.4	0.31	7.9	0.25	6.4	CT-100A‡, CT-600-A‡, CT-1550‡, CT-1551‡, CT-2500‡	100	500
PV14-10RX-C				0.200	5.1	#10	M5	0.96	24.4	0.31	7.9	0.25	6.4		100	500
PV14-14RX-L				0.200	5.1	1/4"	M6	1.16	29.5	0.46	11.7	0.37	9.4		50	500
PV14-56RX-L				0.200	5.1	5/16"	M8	1.16	29.5	0.46	11.7	0.37	9.4		50	500
PV14-38RX-L				0.200	5.1	3/8"	M10	1.25	31.8	0.53	13.5	0.42	10.7		50	500
PV10-8RX-L	12 – 10 AWG	4.0 – 6.0	Yellow	0.250	6.4	#8	M4	1.10	27.9	0.31	7.9	0.30	7.6	CT-100A‡, CT-600-A‡, CT-1550‡, CT-1551‡, CT-2500‡	50	500
PV10-10RX-L				0.250	6.4	#10	M5	1.10	27.9	0.31	7.9	0.30	7.6		50	500
PV10-14RX-L				0.250	6.4	1/4"	M6	1.29	32.8	0.52	13.2	0.39	9.9		50	500
PV10-56RX-L				0.250	6.4	5/16"	M8	1.29	32.8	0.52	13.2	0.42	10.7		50	500
PV10-38RX-L				0.250	6.4	3/8"	M10	1.35	34.3	0.58	14.7	0.46	11.7		50	500
PV8-10RX-QY	8 AWG	10.0	Red	0.360	9.1	#10	M5	1.52	38.6	0.47	11.9	0.43	10.9	CT-720 with Die Insert CD-720PV8-2‡, CT-2600 with Die Insert CD-2600-PV8‡	25	250
PV8-14RX-QY				0.360	9.1	1/4"	M6	1.52	38.6	0.47	11.9	0.43	10.9		25	250
PV8-56RX-QY				0.360	9.1	5/16"	M8	1.62	41.2	0.59	15.0	0.51	13.0		25	250
PV8-38RX-QY				0.360	9.1	3/8"	M10	1.62	41.2	0.59	15.0	0.51	13.0		25	250
PV8-12RX-XY				0.360	9.1	1/2"	M12	1.74	44.2	0.82	20.8	0.51	13.0		10	100
PV6-10RX-X	6 AWG	16.0	Blue	0.436	11.1	#10	M5	1.61	40.9	0.47	11.9	0.43	10.9	CT-720 with Die Insert CD-720PV8-2‡, CT-2600 with Die Insert CD-2600-PV6‡	10	100
PV6-14RX-X				0.436	11.1	1/4"	M6	1.61	40.9	0.47	11.9	0.43	10.9		10	100
PV6-56RX-X				0.436	11.1	5/16"	M8	1.73	43.9	0.62	15.8	0.51	13.0		10	100
PV6-38RX-X				0.436	11.1	3/8"	M10	1.73	43.9	0.62	15.8	0.53	13.5		10	100
PV4-14RX-E	4 AWG	25.0	Yellow	0.515	13.1	1/4"	M6	1.87	47.5	0.55	14.0	0.53	13.5	CT-720 with Die Insert CD-720PV8-2‡, CT-2600 with Die Insert CD-2600-PV4‡	20	200
PV4-56RX-E				0.515	13.1	5/16"	M8	1.94	49.3	0.68	17.3	0.53	13.5		20	200
PV4-38RX-E				0.515	13.1	3/8"	M10	1.94	49.3	0.68	17.3	0.53	13.5		20	200
PV4-12RX-E				0.515	13.1	1/2"	M12	2.03	51.6	0.86	21.8	0.53	13.5		20	200
PV2-14RX-XY	2 AWG	35.0	Red	0.632	16.1	1/4"	M6	1.94	49.3	0.68	17.3	0.58	14.7	CT-720 with Die Insert CD-720PV8-2‡, CT-2600 with Die Insert CD-2600-PV2‡	10	100
PV2-56RX-XY				0.632	16.1	5/16"	M8	1.94	49.3	0.68	17.3	0.58	14.7		10	100
PV2-38RX-XY				0.632	16.1	3/8"	M10	1.94	49.3	0.68	17.3	0.58	14.7		10	100
PV2-12RX-XY				0.632	16.1	1/2"	M12	2.03	51.6	0.86	21.8	0.58	14.7		10	100

‡UL and CSA approved tooling/product combinations.

For crimping tool information, see page M.46.

For the full selection of Panduit Crimping Tools see www.panduit.com.

A.
System
Overview

B.
Copper
Systems

C.
Fiber
Optic
Systems

D.
Power
over
Ethernet

E.
Zone
Cabling

F.
Wireless

G.
Outlets

H.
Media
Distribution

I.
Physical
Infrastructure
Management

J.
Overhead &
Underfloor
Routing

K.
Surface
Raceway

L.
Cabinets,
Racks &
Cable
Management

M.
Grounding &
Bonding

N.
Industrial

O.
Labeling &
Identification

P.
Cable
Management
Accessories

Q.
Index