

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Diodes Incorporated](#)
[BAW156T-7](#)

For any questions, you can email us directly:

sales@integrated-circuit.com



**BAS116T, BAW156T,
 BAV170T, BAV199T**


SURFACE MOUNT LOW LEAKAGE DIODE

Features

- Ultra-Small Surface Mount Package
- Very Low Leakage Current
- Lead Free/RoHS Compliant (Note 2)**
- Qualified to AEC-Q101 Standards for High Reliability
- "Green" Device (Notes 3 and 4)

Mechanical Data

- Case: SOT-523
- Case Material: Molded Plastic, "Green" Molding Compound.
- UL Flammability Classification Rating 94V-0
- Moisture Sensitivity: Level 1 per J-STD-020D
- Terminals: Solderable per MIL-STD-202, Method 208
- Lead Free Plating (Matte Tin Finish annealed over Alloy 42 leadframe).
- Polarity: See Diagrams Below
- Marking Information: See Diagrams Below and Page 3
- Ordering Information: See Page 2
- Weight: 0.002 grams (approximate)



Maximum Ratings @ $T_A = 25^\circ\text{C}$ unless otherwise specified

| Characteristic | Symbol | Value | Unit |
|---|---------------------|------------|------|
| Peak Repetitive Reverse Voltage | V_{RRM} | | |
| Working Peak Reverse Voltage | V_{RWM} | 85 | V |
| DC Blocking Voltage | V_R | | |
| RMS Reverse Voltage | $V_{R(\text{RMS})}$ | 60 | V |
| Forward Continuous Current (Note 1) | I_{FM} | 215 125 | mA |
| Single Diode Double Diode | | | |
| Repetitive Peak Forward Current | I_{FRM} | 500 | mA |
| Non-Repetitive Peak Forward Surge Current @ $t = 1.0\mu\text{s}$ | I_{FSM} | 4.0 | A |
| @ $t = 1.0\text{ms}$ | | 1.0 | |
| @ $t = 1.0\text{s}$ | | 0.5 | |

Thermal Characteristics

| Characteristic | Symbol | Value | Unit |
|---|------------------|-------------|------|
| Power Dissipation (Note 1) | P_D | 150 | mW |
| Thermal Resistance Junction to Ambient Air (Note 1) | R_{JJA} | 833 | °C/W |
| Operating and Storage Temperature Range | T_J, T_{STG} | -65 to +150 | °C |

Electrical Characteristics @ $T_A = 25^\circ\text{C}$ unless otherwise specified

| Characteristic | Symbol | Min | Typ | Max | Unit | Test Condition |
|------------------------------------|-------------|-----|-----|----------------------------|----------|--|
| Reverse Breakdown Voltage (Note 5) | $V_{(BR)R}$ | 85 | — | — | V | $I_R = 100\mu\text{A}$ |
| Forward Voltage | V_F | — | — | 0.90 1.0 1.1 1.25 | V | $I_F = 1.0\text{mA}$ $I_F = 10\text{mA}$ $I_F = 50\text{mA}$ $I_F = 150\text{mA}$ |
| Leakage Current (Note 5) | I_R | — | — | 5.0 80 | nA nA | $V_R = 75\text{V}$ $V_R = 75\text{V}, T_j = 150^\circ\text{C}$ |
| Total Capacitance | C_T | — | 2 | — | pF | $V_R = 0, f = 1.0\text{MHz}$ |
| Reverse Recovery Time | t_{rr} | — | — | 3.0 | μs | $I_F = I_R = 10\text{mA}$, $I_{rr} = 0.1 \times I_R, R_L = 100\Omega$ |

Notes:





1. Device mounted on FR-4 PC board with recommended pad layout, which can be found on our website at <http://www.diodes.com/datasheets/ap02001.pdf>.
2. No purposefully added lead.
3. Diodes Inc.'s "Green" policy can be found on our website at http://www.diodes.com/products/lead_free/index.php.
4. Product manufactured with Date Code UO (week 40, 2007) and newer are built with Green Molding Compound. Product manufactured prior to Date Code UO are built with Non-Green Molding Compound and may contain Halogens or Sb_2O_3 Fire Retardants.
5. Short duration pulse test used to minimize self-heating effect.

**BAS116T, BAW156T,
 BAV170T, BAV199T**

Document number: DS30258 Rev. 12 - 2



**BAS116T, BAW156T,
BAV170T, BAV199T**



Ordering Information (Note 6)


| Part Number | Case | Packaging |
|-------------|---------|------------------|
| BAS116T-7-F | SOT-523 | 3000/Tape & Reel |
| BAW156T-7-F | SOT-523 | 3000/Tape & Reel |
| BAV170T-7-F | SOT-523 | 3000/Tape & Reel |
| BAV199T-7-F | SOT-523 | 3000/Tape & Reel |

Notes: 6. For packaging details, go to our website at <http://www.diodes.com/datasheets/ap02007.pdf>.



**BAS116T, BAW156T,
BAV170T, BAV199T**

Marking Information




XX = Product Type Marking Code (See Page 1, e.g. 50 = BAS116T)
YM = Date Code Marking
Y = Year (ex: N = 2002)
M = Month (ex: 9 = September)

Date Code Key

| Year | 2001 | 2002 | 2003 | 2004 | 2005 | 2006 | 2007 | 2008 | 2009 | 2010 | 2011 | 2012 |
|-------|------|------|------|------|------|------|------|------|------|------|------|------|
| Code | M | N | P | R | S | T | U | V | W | X | Y | Z |
| Month | Jan | Feb | Mar | Apr | May | Jun | Jul | Aug | Sep | Oct | Nov | Dec |
| Code | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 0 | N | D |


Package Outline Dimensions



| SOT-523 | | | |
|----------|------|------|------|
| Dim | Min | Max | Typ |
| A | 0.15 | 0.30 | 0.22 |
| B | 0.75 | 0.85 | 0.80 |
| C | 1.45 | 1.75 | 1.60 |
| D | — | — | 0.50 |
| G | 0.90 | 1.10 | 1.00 |
| H | 1.50 | 1.70 | 1.60 |
| J | 0.00 | 0.10 | 0.05 |
| K | 0.60 | 0.80 | 0.75 |
| L | 0.10 | 0.30 | 0.22 |
| M | 0.10 | 0.20 | 0.12 |
| N | 0.45 | 0.65 | 0.50 |
| α | 0° | 8° | — |

All Dimensions in mm

Suggested Pad Layout



| Dimensions | Value (in mm) |
|------------|---------------|
| Z | 1.8 |
| X | 0.4 |
| Y | 0.51 |
| C | 1.3 |
| E | 0.7 |

IMPORTANT NOTICE

Diodes Incorporated and its subsidiaries reserve the right to make modifications, enhancements, improvements, corrections or other changes without further notice to any product herein. Diodes Incorporated does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold Diodes Incorporated and all the companies whose products are represented on our website, harmless against all damages.

LIFE SUPPORT

Diodes Incorporated products are not authorized for use as critical components in life support devices or systems without the expressed written approval of the President of Diodes Incorporated.