

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Nearson Inc.](#)
[EMFLX-M10004-GPI](#)

For any questions, you can email us directly:

sales@integrated-circuit.com



New Product Data Sheet



e/m-Flex™ EMFLX-M10004-GPI

2dB Ground Plane Independent Antenna

132-174 MHz

- High Performance, Broadband Impedance Match
- Optimized VSWR for Maximum “No Ground Plane” Efficiency
- Black Chrome Finish with Flexible Polymer Alloy Spring
- O-ring Seals for Waterproof Construction
- Durable Xenoy™ Base with TPV Molded Dust Seal and Grip Ring

Electrical Specifications

Frequency Band	132-174 MHz (Tunable Range)
Operational Bandwidth	15-20 MHz (frequency dependent)
VSWR	<1.2:1 at center frequency
	<2:1 across operational bandwidth
Impedance	50Ω
Gain	2 dBi
Power Rating	150 W
Polarization	Linear, Vertical
E-Plane	70 Degrees, Nominal
H-Plane	Omnidirectional

Mechanical Specifications

Overall Length (max)	50 in. (1.27 m)
Whip Material, Finish	17-7 SS, Black Chrome
Base Material	Xenoy™ w/TPV over mold grip ring
Mounting Application	¾ inch thru-hole NMO Mount
Spring Material	Black Molded Polymer Alloy
NMO Cable Assembly & Connector	Sold separately
Operating Temperature	-40° to 85° C
Corrosion	Salt Fog
Humidity	95%

Specifications subject to change without notification.

ELECTRO-MAGWAVE, INC.

6111 Carey Drive, Unit #1, Valley View, Ohio 44125 t 216-453-1160 f 216-447-8828 www.emwaveinc.com