



**CY2XF327FLXCT** Status: **In Production**

[Alert me about changes to this product](#)

[SHARE](#)

- [Datasheet](#)
  - [Inventory](#)
  - [Packaging/Ordering](#)
- [Quality and RoHS](#)
  - [Technical Documents](#)
  - [Related Products](#)
- [Support and Community](#)



CY2XF327FLXCT	
Automotive Qualified	N
Output Signal Type	CMOS
Min. Operating Voltage (V)	2.38
Max. Operating Voltage (V)	3.45
Min. Operating Temp. (°C)	0
Max. Operating Temp. (°C)	70
Temp. Classification	Commercial
No. of PLL	1
Input Signal Type	Xtal Inside
Input Frequency Max. (MHz)	N/A
Core Voltage (V)	2.5/3.3
Output Frequency Min. (MHz)	8
Input Frequency Min. (MHz)	N/A
Output Frequency Max. (MHz)	200
Spread Spectrum	N
No. of Outputs	1
I/O Voltage (V)	2.5/3.3

Pricing & Inventory Availability					
1-9 unit Price*	10-24 unit Price*	25-99 unit Price*	100-249 unit Price*	250-999 unit Price*	1000 + unit Price*
Availability	Quantity	Ships In	Order Now		

\* Prices are shown in United States dollars and are for budgetary use only for volume of 1ku

Packaging/Ordering	
No. of Pins	6
Package Cross Section Drawing	<a href="#">Download</a>
Package Carrier Drawing / Orientation	<a href="#">Package Orientation</a>
Standard Pack Quantity	1000
Minimum Order Quantity (MOQ)	1000
Order Increment	1000
Estimated Lead Time (days)	63

HTS Code	8542.31.0000
ECCN	EAR99

### Quality and RoHS

Moisture Sensitivity Level (MSL)	1
Peak Reflow Temp. (°C)	260 ( <a href="#">Cypress Reflow Profile</a> )
RoHS Compliant	Y <a href="#">Print RoHS Certificate of Compliance</a>
PB Free	Y
Lead/Ball Finish	Ni/Au
Marking	<a href="#">Cypress Marking Format</a>

### Technical Documents

**Application Notes (2)**  
[AN52133 - Frequency Margining using FleXO™ and Its Applications](#) *Last Update: 07/08/2012*  
[AN62914 - Programming FleXO™ Low Noise Clock Generators](#) *Last Update: 03/04/2012*

### Support and Community

- [Cypress Developer Community™](#)
- [Forums](#)
- [Blogs](#)
- [Support](#)
- [Knowledge Base](#)
- [Product Training](#)