

## Excellent Integrated System Limited

Stocking Distributor



Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Weidmüller](#)  
[1770750000](#)

For any questions, you can email us directly:

[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)

Product catalogue | PCB connection systems | PCB plug-in connectors | Pitch 3.50 mm (0.138 inch) | Socket connectors, insulation displacement connection, pitch 3.5 | BLIDCB 3.5 | BLIDCB 3.5F


**General ordering data**

Order No.	1770750000
Part designation	BLIDCB 3.5/3F SN SW
Version	PCB plug-in connector, Female connectors, IDC terminal, Clamping range, max.: 0.5 mm <sup>2</sup> , Pitch: 3.50 mm, No. of poles: 3, 90°/270°, Box
EAN	4032248174539
Qty.	10 pc(s).

**System parameters**

Conductor connection system	IDC terminal
Outgoing direction of conductor	90°/270°
Pitch	3.5 mm
Pitch in inch	0.138 inch
No. of poles	3
No. of rows	1
Screwdriver blade	0.4 x 2.5
Screwdriver blade standard	DIN 5264-A
L1 in mm	7 mm
L1 in inch	0.276 inch
Electric shock protection to DIN VDE 0470	IP 20
Electric shock protection to DIN VDE 0470	Safe from finger touch

**Material data**

Insulating material	PBT
Colour	black
colour chart	Similar to RAL 9011
Insulating material group	IIIa
Flammability class UL 94	V-0
CTI	>= 200
Contact base material	CuSn
Contact surface	tinned

**Connectable conductors**

Clamping range, min.	0.32 mm <sup>2</sup>
----------------------	----------------------

Product catalogue | PCB connection systems | PCB plug-in connectors | Pitch 3.50 mm (0.138 inch) | Socket connectors, insulation displacement connection, pitch 3.5 | BLIDCB 3.5 | BLIDCB 3.5F

#### Connectable conductors

Clamping range, max.	0.5 mm <sup>2</sup>
AWG, min.	22
AWG, max.	20
Outer diameter of insulation, max.	2.1 mm
Solid, min. H05(07) V-U	0.2 mm <sup>2</sup>
Solid, max. H05(07) V-U	0.5 mm <sup>2</sup>
Flexible, min. H05(07) V-K	0.2 mm <sup>2</sup>
Flexible, max. H05(07) V-K	0.5 mm <sup>2</sup>

#### DIN IEC rating data

Rated current, min. No. pins (Tu=20°C)	6 A
Rated current, max. No. pins (Tu=20°C)	6 A
Rated current, min. No. pins (Tu=40°C)	6 A
Rated current, max. No. pins (Tu=40°C)	5 A
Rated voltage for overvoltage class/pollution severity II/2	320 V
Rated voltage for overvoltage class/pollution severity III/2	160 V
Rated voltage for overvoltage class/pollution severity III/3	160 V
Rated impulse withstand voltage for overvoltage class/pollution severity II/2	2.5 kV
Rated impulse withstand voltage for overvoltage class/pollution severity III/2	2.5 kV
Rated impulse withstand voltage for overvoltage class/pollution severity III/3	2.5 kV
Short-time withstand current resistance	3 x 1s with 60 A

#### CSA rating data

Rated voltage (Use group D)	300 V
Rated current (Use group D)	7 A
AWG conductor (field wiring), min.	22
AWG conductor (field wiring), max.	20

#### UL 1059 rating data

Rated voltage (Use group D)	300 V
Rated current (Use group D)	7 A
AWG conductor, min.	22
AWG conductor, max.	20

#### Approvals

Approvals institutes



#### Classifications

ETIM 2.0	NK
ETIM 3.0	EC001284
eClass 4.1	27-26-07-01

Product catalogue | PCB connection systems | PCB plug-in connectors | Pitch 3.50 mm (0.138 inch) | Socket connectors, insulation displacement connection, pitch 3.5 | BLIDCB 3.5 | BLIDCB 3.5F

**Classifications**

eClass 5.0	27-26-07-01
eClass 5.1	27-26-07-04

**Similar products**

Order No.	Part designation	Version
1751450000	BLIDCB 3.5/2F SN OR	PCB plug-in connector, Female connectors, IDC terminal, Clamping range, max.: 0.5 mm <sup>2</sup> , Pitch: 3.50 mm, No. of poles: 2, 90°/270°, Box
1770740000	BLIDCB 3.5/2F SN SW	PCB plug-in connector, Female connectors, IDC terminal, Clamping range, max.: 0.5 mm <sup>2</sup> , Pitch: 3.50 mm, No. of poles: 2, 90°/270°, Box
1751460000	BLIDCB 3.5/3F SN OR	PCB plug-in connector, Female connectors, IDC terminal, Clamping range, max.: 0.5 mm <sup>2</sup> , Pitch: 3.50 mm, No. of poles: 3, 90°/270°, Box
1751470000	BLIDCB 3.5/4F SN OR	PCB plug-in connector, Female connectors, IDC terminal, Clamping range, max.: 0.5 mm <sup>2</sup> , Pitch: 3.50 mm, No. of poles: 4, 90°/270°, Box
1770760000	BLIDCB 3.5/4F SN SW	PCB plug-in connector, Female connectors, IDC terminal, Clamping range, max.: 0.5 mm <sup>2</sup> , Pitch: 3.50 mm, No. of poles: 4, 90°/270°, Box
1751480000	BLIDCB 3.5/5F SN OR	PCB plug-in connector, Female connectors, IDC terminal, Clamping range, max.: 0.5 mm <sup>2</sup> , Pitch: 3.50 mm, No. of poles: 5, 90°/270°, Box
1770770000	BLIDCB 3.5/5F SN SW	PCB plug-in connector, Female connectors, IDC terminal, Clamping range, max.: 0.5 mm <sup>2</sup> , Pitch: 3.50 mm, No. of poles: 5, 90°/270°, Box
1751490000	BLIDCB 3.5/6F SN OR	PCB plug-in connector, Female connectors, IDC terminal, Clamping range, max.: 0.5 mm <sup>2</sup> , Pitch: 3.50 mm, No. of poles: 6, 90°/270°, Box
1770780000	BLIDCB 3.5/6F SN SW	PCB plug-in connector, Female connectors, IDC terminal, Clamping range, max.: 0.5 mm <sup>2</sup> , Pitch: 3.50 mm, No. of poles: 6, 90°/270°, Box
1751500000	BLIDCB 3.5/7F SN OR	PCB plug-in connector, Female connectors, IDC terminal, Clamping range, max.: 0.5 mm <sup>2</sup> , Pitch: 3.50 mm, No. of poles: 7, 90°/270°, Box
1770790000	BLIDCB 3.5/7F SN SW	PCB plug-in connector, Female connectors, IDC terminal, Clamping range, max.: 0.5 mm <sup>2</sup> , Pitch: 3.50 mm, No. of poles: 7, 90°/270°, Box
1751510000	BLIDCB 3.5/8F SN OR	PCB plug-in connector, Female connectors, IDC terminal, Clamping range, max.: 0.5 mm <sup>2</sup> , Pitch: 3.50 mm, No. of poles: 8, 90°/270°, Box
1770800000	BLIDCB 3.5/8F SN SW	PCB plug-in connector, Female connectors, IDC terminal, Clamping range, max.: 0.5 mm <sup>2</sup> , Pitch: 3.50 mm, No. of poles: 8, 90°/270°, Box