

## Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[On-Shore Technology, Inc.](#)  
[41058.2](#)

For any questions, you can email us directly:

[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)




ON-SHORE TECHNOLOGY, INC.



PTR MESSTECHNIK

SRSL 4-T15



tightening torque/thread 1.0 Nm/M 3 Inspection Test Pattern Size A 4

Type Cat.-No. Qty.p.pck.  
**SRSL 4-T15** 41064.2 green/yellow 100


**Ratings:**

**Dimensions** TS 15  
LxBxH (mm) 32x7x32  
Stripped Length 9 mm

**Max Rated Cross Section**

Single Wire (solid) 0.2-4 mm<sup>2</sup>  
Stranded Wire (flexible) 0.2-4 mm<sup>2</sup>  
Wire Size AWG 22-10

SRSLN 2.5-T32



tightening torque/thread 0.7 Nm/M 2.5 Inspection Test Pattern Size A 3

Type Cat.-No. Qty.p.pck.  
**SRSLN 2.5-T32** 41057.2 green/yellow 100

**Ratings:**

**Dimensions** TS 32  
LxBxH (mm) 44x6x43  
Stripped Length 10 mm

**Max Rated Cross Section**

Single Wire (solid) 0.2-4 mm<sup>2</sup>  
Stranded Wire (flexible) 0.2-2.5 mm<sup>2</sup>  
Wire Size AWG 22-14

EARTH TERMINAL BLOCKS

SRSLN 2.5-T35



tightening torque/thread 0.7 Nm/M 2.5 Inspection Test Pattern Size A 3

Type Cat.-No. Qty.p.pck.  
**SRSLN 2.5-T35** 41058.2 green/yellow 100


**Ratings:**

**Dimensions** TS 35  
LxBxH (mm) 52x6x39  
Stripped Length 10 mm

**Max Rated Cross Section**

Single Wire (solid) 0.2-4 mm<sup>2</sup>  
Stranded Wire (flexible) 0.2-2.5 mm<sup>2</sup>  
Wire Size AWG 22-14

SRSL 2.5-T32



tightening torque/thread 0.7 Nm/M 2.5 Inspection Test Pattern Size A 3

Type Cat.-No. Qty.p.pck.  
**SRSL 2.5-T32** 41055.2 green/yellow 100

**Ratings:**

**Dimensions** TS 32  
LxBxH (mm) 42x6x52  
Stripped Length 10 mm

**Max Rated Cross Section**

Single Wire (solid) 0.2-4 mm<sup>2</sup>  
Stranded Wire (flexible) 0.2-2.5 mm<sup>2</sup>  
Wire Size AWG 22-14