



Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[ITT Cannon, LLC](#)
[CIR030FP-20-11S-F80-T12-12](#)

For any questions, you can email us directly:

sales@integrated-circuit.com



Datasheet for part number CIR030FP-20-11S-F80-T12-12

| |
|---|
| Our Catalog Part Number: CIR030FP-20-11S-F80-T12-12 |
| Brand: VEAM Product Category: Circular Product Line: Veam CIR, VBN, Other Series: CIR / FRCIR |

| | |
|--|--|
| Product Datasheet | |
| SERIES | Connector with Bayonet Coupling |
| Shell Style | Rear Mount Receptacle - Square flange, with rear thread |
| Mounting | Flange with through mounting hole |
| Environmental Class | no endbell |
| Shell Size | 20 |
| Contact Arrangement | 20-11 |
| Total Number of contacts | 13 contacts |
| Number of Contacts Size 16 | 13 contacts size 16 |
| Gender | Socket |
| Contact Type | Crimp for AWG wire (used in F80 insert) |
| Contact Plating | Gold |
| Shell Material | Aluminium alloy |
| Shell Plating | Olive drab chromate over cadmium plating (conductive) |
| Wire Size Cross Section for Contacts with Modification -12 | 0,6 mm ² or AWG 20 |
| Shock Resistance | Waterproof to 10 meters (33 ft) 12 h (14.7 PSI) |
| Coupling | 2000 couplings minimum |
| Service Rating Letter | I |
| Operating Voltage DC | 250 V |
| Operating Voltage AC | 200 V |
| Dielectric strength - Minimum Flashover AC RMS | 1400 V |
| Dielectric strength - Test Voltage AC RMS (Hi Pot) | 1000 V |
| Note | Voltages in excess of 30 V ac or 42.5 V dc are potentially hazardous and care should be taken to ensure that such voltages can't be transmitted in any way to exposed metal parts of the connector body. |
| General | Veam CIR series Connectors are produced in accordance with NATO Standard VG95234, which is based on MIL-C-5015 for physical size, layout and environment requirements. |