

## Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:






[TDK Corporation](#)


[VLF403210MT-100M-CA](#)

For any questions, you can email us directly:

[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)

# VLF403210MT-100M-CA

Applications		Automotive Grade
Feature		Wire Wound
		Magnetic Shield
		Ferrite Core
		AEC-Q200
Series	VLF-M Series / VLF403210MT-CA Type	
Status	PROD	




Size	
Length(L)	4.00mm +/-0.20mm
Width(W)	3.20mm +/-0.20mm
Thickness(T)	1.00mm Max.
Recommended Land Pattern (A)	1.10mm Nom.
Recommended Land Pattern (B)	1.30mm Nom.
Recommended Land Pattern (C)	1.80mm Nom.

Electrical Characteristics	
Inductance	10uH +/-20% at 1MHz
Rated Current (L Change) [Typ.]	780mA (30% Down)
Rated Current (L Change) [Max.]	700mA (30% Down)
Rated Current (Temperature Rise) [Typ.]	1.04A (40degC Rise)
DC Resistance [Nom.]	260mΩ
DC Resistance [Max.]	310mΩ


Other	
Operating Temp. Range (Including Self-Temp. Rise)	-40 to 105degC
Soldering Method	Reflow
AEC Q200	Yes
Packing	Blister (Plastic)Taping [180mm Reel]
Package Quantity	1000Pcs Min.
Weight	0.048g

# VLF403210MT-100M-CA


## Characteristic Graphs (This is reference data, and does not guarantee the product's characteristics.)




VLF403210MT-100M-CA



VLF403210MT-100M-CA




VLF403210MT-100M-CA




VLF403210MT-100M-CA

# VLF403210MT-100M-CA

## Characteristic Graphs (This is reference data, and does not guarantee the product's characteristics.)



VLF403210MT-100M-CA(Amb. Temp. = 20degc)



VLF403210MT-100M-CA(DC = 0A) VLF403210MT-100M-CA(DC = 0.35A)

Temperature Rise by DC
no data available