

Excellent Integrated System Limited

Stocking Distributor






Click to view price, real time Inventory, Delivery & Lifecycle Information:


[TDK Corporation](#)
[CLF7045T-680M-CA](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

CLF7045T-680M-CA

Applications	 Automotive Grade
Feature	 Wire Wound
	 Magnetic Shield
	 Ferrite Core
	 AEC-Q200
Series	CLF-CA Series / CLF7045-CA Type
Status	Production




Size	
Length(L)	7.20mm +/-0.20mm
Width(W)	6.90mm +/-0.20mm
Thickness(T)	4.50mm +/-0.30mm
Recommended Land Pattern (A)	1.70mm Nom.
Recommended Land Pattern (B)	4.40mm Nom.
Recommended Land Pattern (C)	2.20mm Nom.

Electrical Characteristics	
Inductance	68uH +/-20% at 100kHz
Rated Current (L Change) [Typ.]	1.1A (10% Down)
Rated Current (Temperature Rise) [Typ.]	950mA (30degC Rise)
DC Resistance [Nom.]	210mΩ
DC Resistance [Max.]	252mΩ


Other	
Operating Temp. Range (Including Self-Temp. Rise)	-40 to 105degC
Soldering Method	Reflow, Iron Soldering
AEC Q200	Yes
Packing	Blister (Plastic)Taping [330mm Reel]
Package Quantity	1000Pcs Min.
Weight	0.8g

CLF7045T-680M-CA


Characteristic Graphs (This is reference data, and does not guarantee the product's characteristics.)




CLF7045T-680M-CA



CLF7045T-680M-CA




CLF7045T-680M-CA




CLF7045T-680M-CA

CLF7045T-680M-CA

Characteristic Graphs (This is reference data, and does not guarantee the product's characteristics.)




CLF7045T-680M-CA(Amb. Temp. = 20degc)



CLF7045T-680M-CA(DC = 0A)

CLF7045T-680M-CA(DC = 0.475A)



CLF7045T-680M-CA(Amb. Temp. = 20degc)