



**Distributor of ITT Cannon, LLC: Excellent Integrated System Limited**

Datasheet of RMDM-51PH001B - MICRO 51 M 18" YEL ROHS

Contact us: [sales@integrated-circuit.com](mailto:sales@integrated-circuit.com) Website: [www.integrated-circuit.com](http://www.integrated-circuit.com)

---

## **Excellent Integrated System Limited**

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[ITT Cannon, LLC](#)  
[RMDM-51PH001B](#)

For any questions, you can email us directly:

[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)



Datasheet for part number RMDM-51PH001B

|  |
|--|
| Our Catalog Part Number: RMDM-51PH001B                                   |
| Brand: Cannon Product Category: Micro Product Line: Micros Series: MICRO |

|                                 |   |
|---------------------------------|---|
| Product Datasheet               |   |
| Series                          | RoHs - Micro "D" Metal Shell  |
| Arrangement                     | 51 Contact  |
| Gender                          | Pin   |
| Contact Material                | gold plated copper alloy  |
| Contact Typ                     | crimp   |
| Contact Resistance              | 8 milliohms max.  |
| Termination Type                | 18" Min, M16874/4 #26AWG, Yellow  |
| Shell Material                  | RoHs - Aluminum   |
| Shell Finish                    | Nickel  |
| Insulator Material              | RoHs - contact size 9 to 100 = liquid crystalline polymer, contact arrangements 7C2 or 24C4 = Diallyl phthalate |
| Hardware                        | HARDWARE=B .092 dia mtg holes   |
| Coupling                        | Friction Coupling   |
| Current Rating                  | 3 A max.  |
| Dielectric Withstanding Voltage | 600 VAC at sea level<br>150 VAC at 70,00' altitude  |
| Insulator Resistance            | 5000 megohms min.   |
| Thermal Shock                   | -55°/+125°  |
| Physical Shock                  | 50 G's, 3 axes, 6 milisecond duration sawtooth pulse  |
| Vibration                       | 20G's, 10-2000 Hz. 12 hours   |
| Durability                      | 500 cycles of mating and unmating, 500 CPH max.   |
| Moisture Resistance             | Insulator resistance > 100 megohms  |
| SaltSpray                       | 48 hours  |