

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Vishay Semiconductor/Diodes Division](#)
[SB2D-M3/5BT](#)

For any questions, you can email us directly:

sales@integrated-circuit.com



www.vishay.com

SB2D thru SB2M

Vishay General Semiconductor

Surface Mount Glass Passivated Rectifier



DO-214AA (SMB)

FEATURES

- Low profile package
- Ideal for automated placement
- Glass passivated chip junction
- Low forward voltage drop
- Low leakage current
- High forward surge capability
- Meets MSL level 1, per J-STD-020, LF maximum peak of 260 °C
- Material categorization: for definitions of compliance please see www.vishay.com/doc?99912



RoHS
COMPLIANT
HALOGEN
FREE

| PRIMARY CHARACTERISTICS | |
|-------------------------|-----------------|
| $I_{F(AV)}$ | 2.0 A |
| V_{RRM} | 200 V to 1000 V |
| I_{FSM} | 55 A |
| I_R | 1.0 μ A |
| V_F at $I_F = 2.0$ A | 0.86 V |
| T_J max. | 150 °C |
| Package | DO-214AA (SMB) |
| Diode variations | Single die |

TYPICAL APPLICATIONS

For use in general purpose rectification of power supplies, inverters, converters and freewheeling diodes for consumer and telecommunication.

MECHANICAL DATA

Case: DO-214AA (SMB)

Molding compound meets UL 94 V-0 flammability rating
Base P/N-M3 - halogen-free, RoHS compliant, and commercial grade

Terminals: Matte tin plated leads, solderable per J-STD-002 and JESD 22-B102

M3 suffix meets JESD 201 class 1A whisker test

Polarity: Color band denotes the cathode end

| MAXIMUM RATINGS ($T_A = 25$ °C unless otherwise noted) | | | | | | | |
|--|----------------|-------------|------|------|------|------|------|
| PARAMETER | SYMBOL | SB2D | SB2G | SB2J | SB2K | SB2M | UNIT |
| Device marking code | | B2D | B2G | B2J | B2K | B2M | |
| Maximum repetitive peak reverse voltage | V_{RRM} | 200 | 400 | 600 | 800 | 1000 | V |
| Maximum DC forward current (fig. 1) | $I_F^{(1)}$ | 2.0 | | | | | A |
| Peak forward surge current 8.3 ms single half sine-wave superimposed on rated load | I_{FSM} | 55 | | | | | A |
| Operating and storage temperature range | T_J, T_{STG} | -55 to +150 | | | | | °C |

Note

(1) Mounted on 8 mm x 8 mm pad areas, 1 oz. FR4 PCB



www.vishay.com

SB2D thru SB2M

Vishay General Semiconductor

| ELECTRICAL CHARACTERISTICS (T _A = 25 °C unless otherwise noted) | | | | | | |
|--|--|-------------------------|-------------------------------|------|------|------|
| PARAMETER | TEST CONDITIONS | | SYMBOL | TYP. | MAX. | UNIT |
| Instantaneous forward voltage | I _F = 1.0 A | T _A = 25 °C | V _F ⁽¹⁾ | 0.90 | - | V |
| | I _F = 2.0 A | | | 0.96 | 1.15 | |
| | I _F = 1.0 A | T _A = 125 °C | | 0.78 | - | |
| | I _F = 2.0 A | | | 0.86 | 1.05 | |
| Reverse current | Rated V _R | T _A = 25 °C | I _R ⁽²⁾ | 0.15 | 1.0 | μA |
| | | T _A = 125 °C | | 36 | 125 | |
| Typical reverse recovery time | I _F = 0.5 A, I _R = 1.0 A, I _{rr} = 0.25 A | | t _{rr} | 2.0 | | μs |
| Typical junction capacitance | Rated V _R = 4.0 V, 1 MHz | | C _J | 16 | | pF |

Notes

⁽¹⁾ Pulse test: 300 μs pulse width, 1 % duty cycle

⁽²⁾ Pulse test: Pulse width, ≤ 40 ms

| THERMAL CHARACTERISTICS (T _A = 25 °C unless otherwise noted) | | | | | | | | |
|---|---------------------------------|------|------|------|------|------|------|------|
| PARAMETER | SYMBOL | SB2D | SB2G | SB2J | SB2K | SB2M | UNIT | |
| Typical thermal resistance | R _{θJA} ⁽¹⁾ | 70 | | | | | | °C/W |
| | R _{θJM} ⁽¹⁾ | 10 | | | | | | |

Note

⁽¹⁾ Units mounted on PCB with 8.0 mm x 8.0 mm copper pad areas, 1 oz. FR4 PCB; R_{θJA} - junction to ambient R_{θJM} - junction to mount

| ORDERING INFORMATION (Example) | | | | |
|--------------------------------|-----------------|------------------------|---------------|------------------------------------|
| PREFERRED P/N | UNIT WEIGHT (g) | PREFERRED PACKAGE CODE | BASE QUANTITY | DELIVERY MODE |
| SB2J-M3/52T | 0.096 | 52T | 750 | 7" diameter plastic tape and reel |
| SB2J-M3/5BT | 0.096 | 5BT | 3200 | 13" diameter plastic tape and reel |

RATINGS AND CHARACTERISTICS CURVES (T_A = 25 °C unless otherwise noted)




Fig. 1 - Maximum Forward Current Derating Curve




Fig. 2 - Forward Power Loss Characteristics



www.vishay.com

SB2D thru SB2M

Vishay General Semiconductor




Fig. 3 - Typical Instantaneous Forward Characteristics




Fig. 5 - Typical Junction Capacitance




Fig. 4 - Typical Reverse Characteristics





Fig. 6 - Typical Transient Thermal Impedance

PACKAGE OUTLINE DIMENSIONS in inches (millimeters)





Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.