

## Excellent Integrated System Limited

Stocking Distributor


Click to view price, real time Inventory, Delivery & Lifecycle Information:

[SunLED](#)  
[XZFABBA10C](#)





For any questions, you can email us directly:

[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)






❖ **BBA**



**LED is recommended for reflow soldering and soldering profile is shown below.**


**Reflow Soldering Profile for SMD Products (Pb-Free Components)**




- Notes:**
1. Maximum soldering temperature should not exceed 280°C
  2. Recommended reflow temperature: 145°C-280°C
  3. Do not put stress to the epoxy resin during high temperatures conditions




**PACKING & LABEL SPECIFICATIONS**




Inside Label On tape




Outside Label On BAG



Outside Label On 19#Box



Outside Label On 12#Box



**TERMS OF USE**

1. Data presented in this document reflect statistical figures and should be treated as technical reference only.
2. Contents within this document are subject to improvement and enhancement changes without notice.
3. The product(s) in this document are designed to be operated within the electrical and environmental specifications indicated on the datasheet. User accepts full risk and responsibility when operating the product(s) beyond their intended specifications.
4. The product(s) described in this document are intended for electronic applications in which a person's life is not reliant upon the LED. Please consult with a SunLED representative for special applications where the LED may have a direct impact on a person's life.
5. The contents within this document may not be altered without prior consent by SunLED.
6. Additional technical notes are available at <http://www.SunLEDusa.com/TechnicalNotes.asp>