

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Triad Magnetics](#)

[C-60U](#)

For any questions, you can email us directly:

sales@integrated-circuit.com



Inductors

C-60U

Description:

Smoothing chokes are power supply filter chokes having a core with an air gap which prevents saturation at maximum current. Hipot to 1500 VRMS between winding and core for safety.

Electrical Specifications (@25C):

| Current DC Amps | Inductance †† Henries | Resistance Ohms |
|--------------------|--------------------------|--------------------|
| 22.5 | 0.005 | 0.06 |

†† = Inductance tolerance -20%, + 50 %


Dimensions:

Unit: In inches

| A | B | C | D | E |
|-------|------|-------|-------|------|
| 3.750 | 4.50 | 4.187 | 3.750 | 3.50 |




Weight: 12.75 lbs.

Schematic:



RoHS Compliance: As of manufacturing date February 2005, all standard products meet the requirements of 2011/65/EU, known as the RoHS initiative.

* Upon printing, this document is considered "uncontrolled". Please contact Triad Magnetics' website for the most current version.



13/64 X 5/16 4 SLOTS.

Web: www.TriadMagnetics.com
Phone 951-277-0757
Fax 951-277-2757

460 Harley Knox Blvd.
Perris, California 92571

Publish Date: December 4, 2013