

Excellent Integrated System Limited

Stocking Distributor


Click to view price, real time Inventory, Delivery & Lifecycle Information:

[FCI](#)
[H502005000J0G](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

PRODUCT NUMBER	PITCH
H5xx00x000J0G	7.62 mm



Dimension



DIM A	(N-1)×7.62+5.7
DIM B	(N-1)×7.62
DIM C	(N-1)×7.62+6.02
DIM D	N×7.62

N=Number of poles

POLES	Tolerance
2p-6p	±0.20
7p-12p	±0.30
13p-16p	±0.40

PART NO.: H5 xx 0 0 x 0 00J0 G


Solid block	0 Black (RAL9005)	Color	RoHS compliant (lead<4%)
No. of poles	2 Red (RAL3001/D)		In copper Alloy
02 2 poles	3 Orange(RAL2011/P)		
03 3 poles	4 Yellow(RAL1018/A)		
...	5 Green(RAL6018/T)		
16 16 poles	6 Blue (RAL5015/A)		
	8 Grey(RAL7035/D)		
	9 White(RAL1102)		
	C Green(RAL6018/U)		



SECTION P-P

Material:
 ●Item@Top body:Thermoplastic (UL94V-0)
 ●Item@Bottom body:Thermoplastic (UL94V-0)
 ●Item@Terminal lever:Thermoplastic (UL94V-0) Orange (RAL2001/P)
 ●Item@Spring clamp:Stainless Steel
 ●Item@Male contact pin: PbBz (CuSn) Tin plated

Electrical cULus
 ●Voltage rating:300V
 ●Current rating:10A
 ●Solid wire(AWG):12-26
 ●Stranded wire(AWG):12-26
 ●Wire strip length:9-10mm
 ●Withstanding Voltage:1.6KV
 ●Operating temperature:-40°C to +115°C
 ●Safety Approval: cULus



mat'l. code	surface ASME Y14.5	tolerance ASME Y14.5	projection MM	product family TERMINAL BLOCK
ltr ecn no dr date	tolerances unless otherwise specified	angles X±0.5 X.X±0.3 X'±1"	scale	title TERMINAL BLOCK SPRING CLAMP PLUGGABLE PLUG MALE CONNECTOR
		dr EVIN ZHONG 051714		dwg no H5xx00x000J0G
		enr EVIN ZHONG 051714		sheet 1 of 1
		chr HANKE FENG 051714		size A4
		appd SHI JUN 051714		type CUSTOMER Drawing
sheet index	revision sheet 1			