

Excellent Integrated System Limited

Stocking Distributor



Click to view price, real time Inventory, Delivery & Lifecycle Information:

[FCI](#)
[HN02505000J0G](#)




For any questions, you can email us directly:

sales@integrated-circuit.com

PRODUCT NUMBER	PITCH
HNxx50x000J0G	5.08 mm



2P mark



- Material:
- Item①Terminal body:Thermoplastic (UL94V-0)
 - Item②Terminal cover:Thermoplastic (UL94V-0)
 - Item③Insulating spacer:Thermoplastic (UL94V-0)
 - Item④Female contact:PhBz (CuSn) Tin plated
 - Item⑤Spring clamp:Stainless Steel

- Electrical: cULus
- Voltage rating: 300VAC
 - Current rating: 10A
 - Wire range:
 - Solid wire(AWG): 12-26
 - Stranded wire(AWG): 14-26
 - Wire strip length: 9-10mm
 - Withstanding Voltage: 1.6KV
 - Operating temperature: -40°C to +115°C
 - Safety Approval: cULus

DIMENSION

Dim L=N×5.08
Dim B=(N-1)×5.08

N=Number of poles

Poles	Tolerance
2P-6P	±0.15
7P-12P	±0.25
13P-18P	±0.35
19P-24P	±0.40

PART NO.: HN xx 50 x 0 00J0 G

Solid block	No. of poles	Color	RoHS compliant (lead<4%) In copper Alloy
0	2	Black (RAL9005)	
1	2	Red (RAL3001/D)	
2	3	Orange(RAL2011/P)	
3	3	Yellow(RAL1018/A)	
4	...	Green(RAL6018/T)	
5	24	Blue (RAL5015/A)	
6	24	Grey(RAL7035/D)	
7	24	White(RAL1102)	
8	24	Green(RAL6018/U)	

mat'l. code	surface	tolerance	projection	product family
ASME Y14.5	ASME Y14.5	ASME Y14.5	ASME Y14.5	TERMINAL BLOCK
tr	ec	n	dr	date
tolerances unless otherwise specified				
angled		X.±0.5		
X'±1"		X.X±0.3		
dr	EVIN ZHONG	051414		
enr	EVIN ZHONG	051414		
chr	HANKE FENG	051414		
appd	SHI JUN	051414		
sheet index	revision	A		
sheet	1			