

## Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Weidmüller](#)  
[0340820000](#)

For any questions, you can email us directly:  
[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)



#### General ordering data

Order No.	0340820000
Part designation	SAK 70/32 KRG
Version	Feed-through terminal, 70 mm <sup>2</sup> , Screw connection, KrG, Medium yellow, TS 32
EAN	4008190080754
Qty.	10 pc(s).

#### Product notes

Note, technical data	Connection torque H07V-R70 = 12 Nm
----------------------	------------------------------------

#### Additional technical data

Colour of insulating material	Medium yellow
Connection direction	on side
End plate required	Yes
Explosion-tested version "Ex e"	No
Installation advice	TS 32
Insulating material	KrG
Levels cross-connected internally	No
No. of identical terminals	1
No. of levels	1
No. of terminal strips per level	2
Open sides	right
Operating temperature range	- 60 °C, + 130 °C
Type of connection	Screwed
Type of mounting	Snap-on
UL 94 flammability rating of insulation material	5VA
Version	Feed-through terminal

#### CSA rating data

Voltage (CSA)	600 V
CSA current	150 A
Min. cross-section (CSA)	AWG 4
Max. cross-section (CSA)	AWG 2/0

#### Conductors for clamping (additional connection)

Flexible with ferrule, min. (DIN 46228 pt 1)	16 mm <sup>2</sup>
Flexible with ferrule, max. (DIN 46228 pt 1)	35 mm <sup>2</sup>

**Conductors for clamping (rated connection)**

Clamping range, min.	16 mm <sup>2</sup>
Clamping range, max.	70 mm <sup>2</sup>
Type of connection	Screw connection
2nd type of connection	screwed
Connection direction	on side
No. of connections	2
Stripping length	24 mm
Clamping screw	M 8
Blade size	S6 (DIN 6911)
Tightening torque range	6.0...12 Nm
Gauge to IEC 60947-1	B11
Solid, min.	16 mm <sup>2</sup>
Solid, max.	16 mm <sup>2</sup>
Stranded, min.	16 mm <sup>2</sup>
Stranded, max.	70 mm <sup>2</sup>
Flexible, min.	16 mm <sup>2</sup>
Flexible, max.	70 mm <sup>2</sup>
Flexible with ferrule, min. (DIN 46228/1)	16 mm <sup>2</sup>
Flexible with ferrule, max. (DIN 46228/1)	35 mm <sup>2</sup>
Flexible, min., ferrule with plastic collar (DIN 46228 pt 4)	16 mm <sup>2</sup>
Flexible, max., ferrule with plastic collar (DIN 46228 pt 4)	35 mm <sup>2</sup>
AWG conductor size, min.	AWG 4
AWG conductor size, max.	AWG 2/0
AWG conductor size, min.	21.15 mm <sup>2</sup>
AWG conductor size, max.	67.44 mm <sup>2</sup>

**Dimensions**

Width	22 mm
Height of lowest version	79.5 mm
Length	75 mm
TS 32 offset	37.5 mm

**Rating data**

Rated cross-section	70 mm <sup>2</sup>
Rated voltage	1,000 V
Rated impulse voltage	8 kV
Rated current	192 A
Standards	IEC 60947-7-1
Current with max. conductor	192 A
Pollution severity	3

**Strap connection**

Strap 1, max.	6 layers 9 x 0.8
Strap 1, min.	3 layers 9 x 0.8
Strap 2, min.	6 layers 13 x 0.5

**UL rating data**

Voltage (UL)	600 V
Current (UL)	150 A

**UL rating data**

Min. cross-section (UL)	AWG 4
Max. cross-section (UL)	AWG 2/0

**Approvals**

Approvals institutes



**Classifications**

ETIM 2.0	EC000897
ETIM 3.0	EC000897
eClass 4.1	27-14-11-20
eClass 5.0	27-14-11-20
eClass 5.1	27-14-11-20

**Similar products**

Order No.	Part designation	Version
0340870000	SAK 70/32 KRG/BL	Feed-through terminal, 70 mm <sup>2</sup> , Screw connection, KrG, blue, TS 32