

Excellent Integrated System Limited

Stocking Distributor



Click to view price, real time Inventory, Delivery & Lifecycle Information:

[FCI](#)
[T202215100J0G](#)



For any questions, you can email us directly:

sales@integrated-circuit.com

PRODUCT NUMBER	PITCH
T2xx21x000J0G	5.08 mm



RECOMMENDED P.C.B LAYOUT
TOP VIEW



Material:

- Item@Terminal housing :Thermoplastic (UL 94V-0)
- Item@Clamp : Brass , Ni plated
- Item@Solder pin : Brass , Tin plated
- Item@Terminal screw: Steel Zinc plating"- "slot type

Electrical UL

- Voltage rating: 300VAC
- Current rating: 10A
- Wire range:
- Solid wire(AWG): 12-24
- Stranded wire(AWG): 12-24
- Torque(Lb-In): 3.5
- Screw: M2.5
- Wire strip length: 6-7mm
- Withstanding Voltage: 1.6KV
- Operating temperature: -40°C to +115°C
- Soldering temperature: 260°C±5°C/5 Sec
- Safety Approval:

Dimension A&B

DIM A	$N \times 5.08$
DIM B	$(N-1) \times 5.08$

N=Number of poles

Poles	DimA&B Tolerance
2P-8P	±0.15
9P-14P	±0.25
15P-20P	±0.35
21P-24P	±0.40

PART NO.: T2 xx 2 1 x 0 00J0 G

End stackable No. of poles	Body Color	RoHS compliant (lead-free)
02 2 poles	0 Black (RAL9005)	in copper Alloy
03 3 poles	2 Red (RAL3001/D)	
...	3 Orange (RAL2011/P)	
...	4 Yellow (RAL1018/A)	
24 24 poles	5 Green (RAL6018/T)	
	6 Blue (RAL5015/A)	
	8 Grey (RAL7035/D)	
	9 White (RAL1102)	
	C Green (RAL6018/U)	

mat'l. code				surface ASME Y14.5		tolerance ASME Y14.5		projection		product family TERMINAL BLOCK			
ltr	ecn no	dr	date	tolerances unless otherwise specified						title			
				int X±0.5 X.X±0.3 X'±1" X.XX±0.1						TERMINAL BLOCK			
						scale				RISING CLAMP, SOLID BLOCK, 35D WIRE INLET			
				dr	EYIN ZHONG	040714			dwg no		sheet 1 of 1	size	
				engr	EYIN ZHONG	040714			T2xx21x00J0G		A4		
				chr	HANKE FENG	040714							
				appd	SHI JUN	040714							
sheet index	revision	A	1					type		CUSTOMER Drawing			