

Excellent Integrated System Limited

Stocking Distributor





Click to view price, real time Inventory, Delivery & Lifecycle Information:

[FCI](#)
[TJ02A15000J0G](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

PRODUCT NUMBER	PITCH
TJxxA1x000J0G	7.50 mm



Section P-P

Material

- Item ④ Clamp: Brass(CuZn) Ni plated
- Item ⑤ Terminal screw: Steel Zinc plating “-” slot type
- Item ⑥ Female contact: High conductivity copper ,Tin plated
- Item ⑦ Terminal Cover: Thermoplastic (UL94V-0)
- Item ⑧ Terminal housing: Thermoplastic (UL94V-0)

Electrical cULus

- Voltage rating: 300VAC
- Current rating: 20A
- Wire range:
 - Solid wire(AWG): 12-24
 - Stranded wire(AWG): 12-24
- Torque: 5LB-in
- Screw: M3
- Wire strip length: 7-8mm
- Withstanding Voltage: 1.6KV
- Operating temperature: -40°C to +115°C
- Safety Approval: 

DIMENSION

$$\text{Dim } A = (N-1) \times 7.5 + 5.5$$
$$\text{Dim B} = (N-1) \times 7.5$$

N= number of poles

Poles	Tolerance
2p-5p	± 0.15
6p-12p	± 0.25
13p-16p	± 0.35

TJ xx A1x 0 00J0 G

No.	of poles
02	2 poles
03	3 poles
...	...
16	16 poles

Color

0	Black (RAL9005)
2	Red (RAL3001/D)
3	Orange(RAL2011/P)
4	Yellow(RAL1018/A)
5	Green(RAL6018/T)
6	Blue (RAL5015/A)
8	Grey(RAL7035/D)
9	White(RAL1102)
C	Green(RAL6018/U)

RoHS compliant
(lead<4%)
In copper Alloy

mat'l. code					surface ASME Y14.5 ✓ tolerance ASME Y14.5			projection 		product family TERMINAL BLOCK			
ltr	ecn	no	dr	date	tolerances unless otherwise specified					title			
					X.±0.5			MM		TERMINAL BLOCK			
					X.X±0.3					PLUGGABLE, PLUG, WITHOUT FLANGE			
					X.XX±0.1			scale		dwg no sheet 1 of 1 size			
					dr	HANKE FENG	032514			TJxxA1x00JOG		A4	
				engr	HANKE FENG	032514							
				chr	SHI JUN	032514							
				appd	SHI JUN	032514							
sheet index		revision		rebat.	A								
				1.									
						CUSTOMER Drawing							