

Excellent Integrated System Limited





Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[FCI](#)
[VM02355000J0G](#)

For any questions, you can email us directly:
sales@integrated-circuit.com

PRODUCT NUMBER	PITCH
VMxx35x000J0G	3.81 mm



Material:

- Item① Clamp: Steel zinc plated.
- Item② Terminal screw: Steel Zinc plating "-" slot type
- Item③ Female contact: PbZn Tin plated
- Item④ Terminal (top body): Thermoplastic (UL94V-0)
- Item⑤ Terminal (bottom body): Thermoplastic (UL94V-0)
- Item⑥ Clamp cage: Steel Zinc plated

Electrical cULus

- Voltage rating: 300VAC
- Current rating: 10A
- Wire range:
- Solid wire(AWG): 16-28
- Stranded wire(AWG): 16-28
- Torque: 1.7Lb-In
- Screw: M2
- Wire strip length: 6-7mm
- Withstanding Voltage: 1.6KV
- Operating temperature: -40°C to +115°C
- Safety approval:

DIMENSION

Dim L	(N-1)×3.81+4.62
Dim P	(N-1)×3.81

N=Number of poles

Poles	Tolerance
2p-6p	±0.20
7p-12p	±0.25
13p-18p	±0.30
19p-24p	±0.40

PART NO.: VM xx 35 x 0 00J0 G

- | | | | |
|--------------|----------|---------------------|-----------------|
| | | Color | RoHS compliant |
| Solid block | 0 | Black (RAL9005) | (lead<4%) |
| No. of poles | 2 | Red (RAL3001/D) | In copper Alloy |
| 02 | 2 poles | 3 Orange(RAL2011/P) | |
| 03 | 3 poles | 4 Yellow(RAL1018/A) | |
| ... | ... | 5 Green(RAL6018/T) | |
| 24 | 24 poles | 6 Blue (RAL5015/A) | |
| | | 8 Grey(RAL7035/D) | |
| | | 9 White(RAL1102) | |
| | | C Green(RAL6018/U) | |

mat'l. code	surface ASME Y14.5	tolerance ASME Y14.5	projection	product family TERMINAL BLOCK
ltr	ecn	no	dr	date
tolerances unless otherwise specified				title TERMINAL BLOCK PLUGGABLE PLUG, WITHOUT FLANGE
angles	X.±0.5		MM	scale
X'±1'	X.X±0.3			
	X.XX±0.1			
dr	EVIN ZHONG	041914		dwg no
engr	EVIN ZHONG	041914		sheet 1 of 1
chr	HANKE FENG	041914		size A4
appd	SHI JUN	041914		type CUSTOMER Drawing
sheet index	revision sheet	A 1		