

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[FCI](#)

[YK32102030J0G](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

PRODUCT NUMBER		PITCH	
YK321xx0x0J0G		7.62mm	

SECTION P-P

RECOMMENDED P.C.B LAYOUT
TOP VIEW

MATERIALS & ELECTRICAL

RATED VOLTAGE & CURRENT: 300V, 15 A

WITHSTAND VOLTAGE: AC 2000 V/Min

INSULATION RESISTANCE: 1000 MΩ OR MORE AT DC 500 V

OPERATING TEMPERATURE RANG: -40 °C ~ +115 °C

SCREW TORQUE VALUE: 5.2 Lb-In

WIRE RANGE: 22 - 14 AWG

1) HOUSING: THERMOPLASTIC, UL 94 V-0 BLACK

2) TERMINAL: BRASS, 0.8t

3) TERMINAL SCREWS: STEEL, #5-40

Safety Approval:

PART NO.: YK 321xx 0 x 0 J0G

No. of poles

02 2 poles

03 3 poles

... ..

30 30 poles

Plated

Code	Terminal	Screw
0	G/F	G/F
1	G/F	Zinc
2	Tin	G/F
3	Tin	Zinc

RoHS compliant
(lead<4%)
In copper Alloy

DIMENSION

Dim A	N×7.62±0.86
Dim B	(N-1)×7.62

N=Number of poles

Poles	Tolerance
2p-4p	±0.20
5p-21p	±0.30
22p-30p	±0.50

mat'l. code	surface	tolerance	projection	product family
ltr ecn no dr date	ASME Y14.5	ASME Y14.5	MM	TERMINAL BLOCK
	tolerances unless otherwise specified			
	angles	X.±0.5		
	X'±1°	X.X±0.3		
		X.XX±0.1		
dr	EVAN LU	061014		
enr	EVAN LU	061014		
chr	HANKE FENG	061014		
appd	SHI JUN	061014		
sheet index	revision sheet	A 1		