


## Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Weidmüller](#)  
[1768320000](#)

For any questions, you can email us directly:  
[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)


**General ordering data**

Order No.	1768320000
Part designation	ZDU 16/3AN
Version	Feed-through terminal, 16 mm <sup>2</sup> , Tension clamp connection, Wemid, dark beige, TS 35
EAN	4032248122813
Qty.	20 pc(s).

**Product notes**

Product description	Z-series standard ranges provide solutions for conductor cross-sections from 0.05 to 35 mm <sup>2</sup> .
---------------------	---

**PT OKIECEEx/ATEX rating data**

EU-type examination certificate	KEMA00ATEX2107U
Download, German	KEMA00ATEX2107U_d.pdf
Download English	KEMA00ATEX2107U_e.pdf
IECEX Certificate of Conformity	IECEXULD05.0009U
ATEX voltage	550 V
ATEX current	66 A
ATEX conductor cross-section	16 mm <sup>2</sup>
IECEX voltage	550 V
IECEX current	63 A
IECEX conductor cross-section	16 mm <sup>2</sup>
Voltage when using cross-connections	CrossConnectionGuide.pdf
Operating temperature range	Einsatztemperaturbereich siehe EG-Baumusterprüfbescheinigung/IECEX-Certificate of Conformity
Marking EN 60079-7	Ex e II
Marking ATEX Directive 94/9/EC	Ex II 2 G D

**Additional technical data**

Colour of insulating material	dark beige
Connection direction	top
End plate required	Yes
Explosion-tested version "Ex e"	Yes

**Additional technical data**

Installation advice	TS 35
Insulating material	Wemid
Levels cross-connected internally	No
No. of identical terminals	1
No. of levels	1
No. of terminal strips per level	3
Open sides	right
Operating temperature range	- 50 °C, + 120 °C
Product family	Z-series
Type of connection	Clamped
Type of mounting	Snap-on
UL 94 flammability rating of insulation material	V-0
Version	Feed-through terminal

**CSA rating data**

Voltage (CSA)	600 V
CSA current	65 A
Min. cross-section (CSA)	AWG 14
Max. cross-section (CSA)	AWG 4

**Conductors for clamping (additional connection)**

Flexible with ferrule, min. (DIN 46228 pt 1)	1.5 mm <sup>2</sup>
Flexible with ferrule, max. (DIN 46228 pt 1)	16 mm <sup>2</sup>

**Conductors for clamping (rated connection)**

Clamping range, min.	1.5 mm <sup>2</sup>
Clamping range, max.	25 mm <sup>2</sup>
Type of connection	Tension clamp connection
2nd type of connection	clamped
Connection direction	top
No. of connections	3
Stripping length	18 mm
Blade size	1.0 x 5.5 mm
Gauge to IEC 60947-1	A7
Solid, min.	1.5 mm <sup>2</sup>
Solid, max.	16 mm <sup>2</sup>
Stranded, min.	1.5 mm <sup>2</sup>
Stranded, max.	25 mm <sup>2</sup>
Flexible, min.	1.5 mm <sup>2</sup>
Flexible, max.	16 mm <sup>2</sup>
Flexible with ferrule, min. (DIN 46228/1)	1.5 mm <sup>2</sup>
Flexible with ferrule, max. (DIN 46228/1)	16 mm <sup>2</sup>
Flexible, min., ferrule with plastic collar (DIN 46228 pt 4)	1.5 mm <sup>2</sup>
Flexible, max., ferrule with plastic collar (DIN 46228 pt 4)	16 mm <sup>2</sup>
AWG conductor size, min.	AWG 14
AWG conductor size, max.	AWG 4
AWG conductor size, min.	2.08 mm <sup>2</sup>
AWG conductor size, max.	21.15 mm <sup>2</sup>

**Conductors for clamping (rated connection)**
**Dimensions**

Width	12.1 mm
Height of lowest version	51.5 mm
Length	99 mm
TS 35 offset	42 mm

**Rating data**

Rated cross-section	16 mm <sup>2</sup>
Rated voltage	800 V
Rated impulse voltage	8 kV
Rated current	76 A
Standards	IEC 60947-7-1
Current with max. conductor	76 A
Pollution severity	3

**UL rating data**

Voltage (UL)	600 V
Current (UL)	65 A
Min. cross-section (UL)	AWG 14
Max. cross-section (UL)	AWG 4

**Approvals**

Approvals institutes


**Downloads**

STEP	1768320000_29594_ZDU_16-3AN_STP.stp
------	-------------------------------------

**Classifications**

eClass 4.1	27-14-11-20
eClass 5.0	27-14-11-20
eClass 5.1	27-14-11-20

**Similar products**

Order No.	Part designation	Version
1745230000	ZDU 16	Feed-through terminal, 16 mm <sup>2</sup> , Tension clamp connection, Wemid, dark beige, TS 35
1745240000	ZDU 16 BL	Feed-through terminal, 16 mm <sup>2</sup> , Tension clamp connection, Wemid, blue, TS 35

1768330000 ZDU 16/3AN BL

Feed-through terminal, 16 mm<sup>2</sup>, Tension clamp connection, Wemid, blue, TS 35