


Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Weidmüller](#)
[1771360000](#)

For any questions, you can email us directly:
sales@integrated-circuit.com



General ordering data

Order No.	1771360000
Part designation	ZPE 6-2/3AN
Version	Earth terminal, 6 mm ² , Tension clamp connection, Wemid, green/yellow, TS 35
EAN	4032248142958
Qty.	50 pc(s).

Product notes

Product description	The compact terminal range for conductor cross-sections 0.13 to 16 mm ²
---------------------	--

PT OKIECEEx/ATEX rating data

EU-type examination certificate	KEMA97ATEX4677U
Download, German	KEMA97ATEX4677U_d.pdf
Download English	KEMA97ATEX4677U_e.pdf
ATEX conductor cross-section	6 mm ²
Voltage when using cross-connections	CrossConnectionGuide.pdf
Operating temperature range	Einsatztemperaturbereich siehe EG-Baumusterprüfbescheinigung/IECEX-Certificate of Conformity
Marking EN 60079-7	Ex e II
Marking ATEX Directive 94/9/EC	Ex II 2 G D

Additional technical data

Colour of insulating material	green/yellow
Connection direction	Inclined / angled
End plate required	Yes
Explosion-tested version "Ex e"	Yes
Installation advice	TS 35
Insulating material	Wemid
Levels cross-connected internally	No
No. of identical terminals	1
No. of levels	1
No. of terminal strips per level	3

Additional technical data

Open sides	right
Operating temperature range	- 50 °C, + 120 °C
Product family	Z-series
Type of connection	Clamped
Type of mounting	Snap-on
UL 94 flammability rating of insulation material	V-0
Version	PE terminal

CSA rating data

Min. cross-section (CSA)	AWG 20
Max. cross-section (CSA)	AWG 8

Conductors for clamping (additional connection)

Flexible with ferrule, min. (DIN 46228 pt 1)	0.5 mm ²
Flexible with ferrule, max. (DIN 46228 pt 1)	6 mm ²

Conductors for clamping (rated connection)

Clamping range, min.	0.22 mm ²
Clamping range, max.	10 mm ²
Type of connection	Tension clamp connection
2nd type of connection	clamped
Connection direction	Inclined / angled
No. of connections	3
Stripping length	12 mm
Blade size	0.6 x 3.5 mm
Gauge to IEC 60947-1	A5
Solid, min.	0.5 mm ²
Solid, max.	10 mm ²
Flexible, min.	0.5 mm ²
Flexible, max.	10 mm ²
Flexible with ferrule, min. (DIN 46228/1)	0.5 mm ²
Flexible with ferrule, max. (DIN 46228/1)	6 mm ²
Flexible, min., ferrule with plastic collar (DIN 46228 pt 4)	0.5 mm ²
Flexible, max., ferrule with plastic collar (DIN 46228 pt 4)	6 mm ²
AWG conductor size, min.	AWG 22
AWG conductor size, max.	AWG 8
AWG conductor size, min.	0.33 mm ²
AWG conductor size, max.	8.37 mm ²

Dimensions

Width	8.1 mm
Height of lowest version	50 mm
Length	68 mm
TS 35 offset	39.5 mm

PE rating data

PEN function	No
Pollution severity	3

PE rating data

Rated cross-section	6 mm ²
Rated impulse withstand voltage to adjacent terminal	8 kV
Rated short-time current	720 A (6 mm ²)
Rated voltage for adjacent terminal	800 V
Standards	IEC 60947-7-2

UL rating data

Min. cross-section (UL)	AWG 22
Max. cross-section (UL)	AWG 8

Approvals

Approvals institutes



Classifications

eClass 4.1	27-14-03-05
eClass 5.0	27-14-03-05
eClass 5.1	27-14-03-05

Similar products

Order No.	Part designation	Version
1771370000	ZPE 6-2/2AN	Earth terminal, 6 mm ² , Tension clamp connection, Wemid, green/yellow, TS 35