

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Triad Magnetics](#)

[F-8X](#)

For any questions, you can email us directly:

sales@integrated-circuit.com



POWER TRANSFORMER
Chassis Mount: Single Secondary

F-8X

Electrical Specifications (@25C)

1. Maximum Power: 30.0 VA
2. Primary: 115V 50/60 Hz
3. Secondary: 5.0VCT @ 6.0 Amps
4. Voltage Regulation: 15 % TYP @ full load to no load
5. Temperature Rise: 35C TYP (45C MAX allowed)

Description:

The F-8X is part of a series which has a long history of reliable service in the field, made from a proven design and constructed with UL recognized materials.

Construction:

Wound on a single channel nylon bobbin. Materials are UL recognized, Class B (130° C) rated.

Safety:


These products are 100% hipot tested with an insulation of 1500V between primary and secondary windings as well as between the primary / secondary windings and the core.

Dimensions: Units: In inches

A	B	C	D
2.281	3.750	2.125	3.125

Mounting Hole Diameter: .187 in
Lead length: 7.0 inches ± 1 inch
Weight: 1.70 lbs

Schematic:



Primary: Black to Black
Secondary: Yellow to Yellow

RoHS Compliance: As of manufacturing date February 2005, all standard products meet the requirements of 2011/65/EU, known as the RoHS initiative.

* Upon printing, this document is considered "uncontrolled". Please contact Triad Magnetics' website for the most current version.

