

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Wiha](#)
[32505](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

Go To
Image Index

Go To
Numerical Index

Wiha Quality Tools
Germany




www.wihatools.com

Wiha Insulated TORX® Screwdrivers




325 TORX® Screwdriver, With Wiha-SoftFinish® Handle
Insulation According to ASTM F-1505-01, New VDE Specification 0682/part 201 and EN/IEC 60900, NFPA70E, Δ up to 1000 Volt.
Individually Tested. Blade high alloy cvm steel, hardened, black finish. Insulation molded directly onto blade.

Item	⊛	—	—	—	—	—	—
No.	Size	mm	Inch	mm	Inch	lbs.	pkg.
325 05	T5	60	2.4	164	6.5	.06	10
325 11	T6	60	2.4	164	6.5	.06	10
325 16	T7	60	2.4	164	6.5	.06	10
325 21	T8	60	2.4	164	6.5	.06	10
325 26	T9	60	2.4	164	6.5	.06	10
325 31	T10	60	2.4	164	6.5	.06	10
325 36	T15	80	3.1	191	7.5	.12	10
325 41	T20	80	3.1	191	7.5	.12	10
325 46	T25	80	3.1	198	7.8	.17	10
325 51	T27	100	3.9	218	8.6	.20	10
325 56	T30	100	3.9	218	8.6	.20	10
325 61	T40	150	5.9	274	10.8	.30	10



325 90 Set 6 Pcs. TORX®

Item	⊛	—	⊛	—	↺
No.	Size	mm	Size	mm	lbs.
325 90	325 21	T8 60	325 36	T15 80	.83
	325 26	T9 60	325 41	T20 80	
	325 31	T10 60	325 46	T25 80	




325 92 Set 10 Pcs. TORX®

Item	⊛	—	⊛	—	↺
No.	Size	mm	Size	mm	lbs.
325 92	325 11	T6 60	325 36	T15 80	1.2
	325 16	T7 60	325 41	T20 80	
	325 21	T8 60	325 46	T25 80	
	325 26	T9 60	325 51	T27 100	
	325 31	T10 60	325 56	T30 100	

Insulated Terminal Block Xeno Screwdrivers

Combination Slotted/Phillips Terminal Block Drivers



307 Combination Terminal Block Xeno Screwdriver, With Wiha SoftFinish® Handle Insulation According to ASTM F-1505-01, New VDE Specification 0682/part 201 and EN/IEC 60900, NFPA70E. Individually Tested. Blade CVM steel, hardened, black finish. Insulation molded directly onto blade. Wiha-SoftFinish® handle, multi-component, cushion grip. For combination Slotted/Phillips head terminal screws.


Item	⊕	—	—	—	↺	—
No.	Size	mm	mm	Inch	lbs.	pkg.
307 00	1	80	191	7.5	1.23	10
307 01	2	100	218	8.6	1.23	10

Wiha Insulated Square Tip Screwdrivers



358 Square Tip Screwdriver, With Wiha-SoftFinish® Handle Insulation According to ASTM F-1505-01, New VDE Specification 0682/part 201 and EN/IEC 60900, NFPA70E, Δ up to 1000 Volt. Individually Tested. Blade high alloy cvm steel, hardened, black finish. Insulation molded directly onto blade.

Item	⊙	—	—	—	↺	—
No.	Size	mm	Inch	mm	Inch	lbs.
358 11	1	100	4.0	210	8.2	.12 10
358 12	2	150	6.0	268	10.5	.19 10



358 90 Set 6 Pcs. Insulated Slotted, Phillips & Square Drivers

Item	⊕	—	⊙	—	↺
No.	Size	mm	mm	mm	lbs.
358 90	321 01	1 80	320 24	4.5 125	.83
	321 02	2 100	320 39	6.5 150	
	358 11	1 100			
	358 12	2 150			

PREVIOUS

NEXT

INDEX