

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Semtech](#)
[USC1306](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

SEMTECH

RECTIFIER, up to 400V, 5A, 50ns

**USC1304
USC1305
USC1306**

January 7, 1998

TEL:805-498-2111 FAX:805-498-3804 WEB:http://www.semtech.com

**AXIAL LEADED HERMETICALLY SEALED
SUPERFAST RECTIFIER DIODE**

**QUICK
REFERENCE DATA**

- Very low reverse recovery time
- Hermetically sealed with Metoxilite fused metal oxide
- Low thermal impedance
- Low switching losses
- Soft, non-snap off, recovery characteristics

- $V_R = 200 - 400V$
- $I_F = 5.0A$
- $t_{rr} = 50nS$
- $I_R = 20\mu A$

ABSOLUTE MAXIMUM RATINGS (@ 25°C unless otherwise specified)

	Symbol	USC1304	USC1305	USC1306	Unit
Working reverse voltage	V_{RWM}	200	300	400	V
Repetitive reverse voltage	V_{RRM}	200	300	400	V
Average forward current (@ 55°C, lead length = 0.375")	$I_{F(AV)}$	←	5.0	→	A
Repetitive surge current (@ 55°C in free air, lead length 0.375")	I_{FRM}	←	16	→	A
Non-repetitive surge current ($t_p = 8.3mS$, @ V_R & T_{jmax})	I_{FSM}	←	70	→	A
Storage temperature range	T_{STG}	←	-55 to +150	→	°C
Operating temperature range	T_{OP}	←	-55 to +150	→	°C

MECHANICAL

G4

DIM #	MM		INCHES		NOTE
	MIN	MAX	MIN	MAX	
A	3.4	4.6	.135	.180	-
B	22.9	33.0	.90	1.30	-
C	3.5	4.2	.140	.165	-
D	-	.80	-	.030	1
E	.91	1.07	.036	.042	-

NOTES:
1. LEAD DIAMETER UNCONTROLLED OVER THIS REGION.

Weight = 0.04oz

SEMTECH

RECTIFIER, up to 400V, 5A, 50ns

USC1304
 USC1305
 USC1306

January 7, 1998

ELECTRICAL CHARACTERISTICS (@ 25°C unless otherwise specified)

	Symbol	USC1304	USC1305	USC1306	Unit
Average forward current max. (pcb mounted; $T_A = 55^\circ\text{C}$) for sine wave	$I_{F(AV)}$	←	2.9	→	A
	$I_{F(AV)}$	←	3.0	→	A
Average forward current max. ($T_L = 55^\circ\text{C}$; $L = 3/8''$) for sine wave	$I_{F(AV)}$	←	4.9	→	A
	$I_{F(AV)}$	←	5.0	→	A
I^2t for fusing ($t = 8.3\text{mS}$) max.	I^2t	←	20	→	A^2S
Forward voltage drop max. @ $I_F = 3.0\text{A}$, $T_j = 25^\circ\text{C}$	V_F	←	1.25	→	V
Reverse current max. @ V_{RWM} , $T_j = 25^\circ\text{C}$ @ V_{RWM} , $T_j = 100^\circ\text{C}$	I_R	←	20	→	μA
	I_R	←	500	→	μA
Reverse recovery time max. 0.5A I_F to 1.0A I_R . Recovers to 0.25A I_{RR} .	t_{rr}	←	50	→	nS
Junction capacitance typ. @ $V_R = 10\text{V}$, $f = 1\text{MHz}$	C_j	←	90	→	pF

THERMAL CHARACTERISTICS

	Symbol	USC1304	USC1305	USC1306	Unit
Thermal resistance - junction to lead Lead length = 0.375"	$R_{\theta JL}$	←	20	→	$^\circ\text{C/W}$
	$R_{\theta JL}$	←	5	→	$^\circ\text{C/W}$
Thermal resistance - junction to amb. on 0.06" thick pcb. 1 oz. copper.	$R_{\theta JA}$	←	75	→	$^\circ\text{C/W}$