

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[3M](#)
[829-5](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

Scotch® Packing List Pouch Tape 829



Technical Data

May, 2003

Product Description

Scotch® Packing List Pouch Tape 829 is a pressure-sensitive tape with a red border framing a non-sticky, clear, rectangular center window, which allows attaching and protecting of packing lists and other documents to boxes and shipping containers.

Construction

Backing	Biaxially oriented polypropylene film
Adhesive	Pressure sensitive hot melt rubber-resin
Colors	Clear with red print



Each pouch is 5 in. high x 6 in. long
Window (Non-sticky) 3¾ in. high x 4⅝ in. long

Typical Physical Properties

Note: The following technical information and data should be considered representative or typical only, and should not be used for specification purposes.

		ASTM Test Method
Adhesion to Steel:*	40 oz./in. width (44 N/100 mm width)	D-3330
Tensile Strength:		
Machine Direction:	22 lbs./in. width (385 N/100 mm width)	D-3759
Cross Direction:	44 lbs./in. width (771 N/100 mm width)	D-3759
Elongation at Break:	160%	D-3759
Thickness - Backing:	1.2 mil (0.030 mm)	D-3652
Total:	1.9 mil (0.051 mm)	D-3652
Holding Power to Fiberboard:*	3,000 + minutes	D-3654

*Valid only for border area, not window.

Features

- Clear with red border and standard message: “Packing List Enclosed” and “Cut Here” printed near cross-web dots (dispense line).
- Adheres instantly to a variety of surfaces.
- Edge tear and split resistance.
- Good adhesion to fiberboard.
- Complies with the environmental considerations of ASTM D 1974.
- Strong film cover protects documents from weather or abrasion.
- Read-through of enclosed documents.
- Fast application saves time.
- Keeps packing list or label securely with the package.
- Conformable backing.

Scotch® Packing List Pouch Tape

829

Application Techniques The Scotch® Tape Dispensers M727 and M797 are recommended for Scotch® Packing List Pouch Tape 829.

Storage Conditions Store in a clean, dry place. Temperature of 40-80°F (4-26°C) and 40-50% relative humidity are recommended.

For Additional Information To request additional product information or to arrange for sales assistance, call toll free 1-800-362-3550 or visit www.3M.com/packaging. Address correspondence to: 3M Industrial Adhesives and Tapes Division, Building 21-1W-10, 900 Bush Avenue, St. Paul, MN 55144-1000. Our fax number is 651-778-4244. In Canada, phone: 1-800-364-3577. In Puerto Rico, phone: 1-787-750-3000. In Mexico, phone: 52-70-04-00.

Important Notice 3M MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's application. Please remember that many factors can affect the use and performance of a 3M product in a particular application. The materials to be bonded with the product, the surface preparation of those materials, the product selected for use, the conditions in which the product is used, and the time and environmental conditions in which the product is expected to perform are among the many factors that can affect the use and performance of a 3M product. Given the variety of factors that can affect the use and performance of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for the user's application.

Limitation of Remedies and Liability If the 3M product is proved to be defective, THE EXCLUSIVE REMEDY, AT 3M'S OPTION, SHALL BE TO REFUND THE PURCHASE PRICE OF OR TO REPAIR OR REPLACE THE DEFECTIVE 3M PRODUCT. 3M shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental, or consequential, regardless of the legal theory asserted, including, but not limited to, contract, negligence, warranty, or strict liability.



This Industrial Adhesives and Tapes Division product was manufactured under a 3M quality system registered to ISO 9002 standards.



**Industrial Business
Industrial Adhesives and Tapes Division**

3M Center, Building 21-1W-10, 900 Bush Avenue
St. Paul, MN 55144-1000



*Recycled Paper
40% pre-consumer
10% post-consumer*

Printed in U.S.A.
©3M 2003 70-0710-0257-3 (5/03)