

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Mallory Sonalert Products](#)
[SCE028LD2DT1B](#)

For any questions, you can email us directly:
sales@integrated-circuit.com

MALLORY

Mallory Sonalert Products Inc.

Part # **SCE028LD2DT1B**

Sales Outline Drawing

Revision **A**

Specifications:

| | |
|------------------------------|--|
| Sound Level Category | Loud |
| Mode of Operation | Dual Tone |
| Voltage Rating | 10 to 28 Vdc |
| Frequency | 2000 - 1600 Hz |
| Loudness @ 2 FT | 85 to 95 dB(A) typ. |
| Current Draw | 20 mA Max |
| Housing Material | Nylon 6/6 (Color: Black) |
| Storage Temperature | -40°C to +85°C |
| Operating Temperature | -30°C to +65°C |
| Panel Mounting | Recommended hole size is 1.25in (31.75mm). Threaded front will fit standard 30mm (1.181in) hole. |
| Knurled Nut | Used to attach part to panel. The max recommended torque is 10 in-lbs |
| Termination | 5mm standard socket used with pluggable screw terminal block. |
| Weight (Typical) | 1.05 oz (30 g) |
| NEMA 3R, 4X, & 12 | Approved with use of ACC03. |
| Options | For other options contact factory |

Dimensions: Inches (mm)

RoHS Compliant

