

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[FCI](#)




[68118-006](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

PRODUCT NO		REVOLUTIONS					
68118		REV	DESCRIPTION	BY	DATE		
		G	REVISED AND REWORKED PER EIA-609	Lang	5/16/06		
		H	REVISED NO. 0131	Lang	5/16/06		

PRODUCT NO.	NO. OF POSITION	A	B	C	D	E	F
68118-006	6	11.88 / .468	10.68 / .420	7.78 / .306	6.35 / .250	7.90 / .314	9.28 / .365
-008	8	14.42 / .568	13.22 / .520	10.32 / .406	8.89 / .350	10.52 / .414	11.82 / .465
-010	10	16.98 / .668	15.78 / .620	12.86 / .506	11.43 / .450	13.06 / .514	14.36 / .565
-014	14	22.04 / .868	20.84 / .820	17.94 / .706	16.51 / .650	18.14 / .714	19.44 / .765
-016	16	24.58 / .968	23.38 / .920	20.48 / .806	19.05 / .750	20.68 / .814	21.98 / .865
-018	18	27.12 / 1.068	25.92 / 1.020	23.02 / .906	21.59 / .850	23.22 / .914	24.52 / .965
-020	20	29.66 / 1.168	28.46 / 1.120	25.56 / 1.006	24.13 / .950	25.76 / 1.014	27.06 / 1.065
-024	24	34.74 / 1.368	33.54 / 1.320	30.64 / 1.206	29.21 / 1.150	30.84 / 1.214	32.14 / 1.265
-026	26	37.28 / 1.468	36.08 / 1.420	33.18 / 1.306	31.75 / 1.250	33.38 / 1.314	34.68 / 1.365
-030	30	42.36 / 1.668	41.16 / 1.620	38.26 / 1.506	36.83 / 1.450	38.46 / 1.514	39.76 / 1.565
-034	34	47.44 / 1.868	46.24 / 1.820	43.34 / 1.706	41.91 / 1.650	43.54 / 1.714	44.84 / 1.765
-040	40	55.05 / 2.168	53.85 / 2.120	50.95 / 2.006	49.53 / 1.950	51.16 / 2.014	52.46 / 2.065
-050	50	67.76 / 2.668	66.56 / 2.620	63.66 / 2.506	62.23 / 2.450	63.86 / 2.514	65.16 / 2.565
-060	60	80.46 / 3.168	79.26 / 3.120	76.36 / 3.006	74.93 / 2.950	76.56 / 3.014	77.86 / 3.065
68118-064	64	85.54 / 3.368	84.34 / 3.320	81.44 / 3.206	80.01 / 3.150	81.64 / 3.214	82.94 / 3.265

NOTES:
 ① SEE TABLE.
 ② MATERIAL: POLYESTER (PET) GLASS 30% FILLED. UL 94V-0. COLOR: BLUE.

ADD 'LF' SUFFIX AT THE END OF PART NUMBER FOR LEAD FREE OPTION. IF 'LF' P/N THE PRODUCT MEETS EUROPEAN UNION DIRECTIVES AND OTHER COUNTRY REGULATION AS DESCRIBED IN 68-22-006. THE HOUSING WILL WITHSTAND EXPOSURE TO 260° PEAK TEMPERATURE FOR 15 SECONDS IN A WAVE SOLDER APPLICATION WITH A 1.5mm MINIMUM THICK CIRCUIT BOARD. SEE APPLICATION NOTES/PROCEDURES IF THEY ARE AVAILABLE.