

Excellent Integrated System Limited

Stocking Distributor


Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Central Semiconductor Corp](#)
[1N4448 TR](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

Central
Semiconductor Corp.
**Central
Semiconductor Corp.**
**CentralTM
Semiconductor Corp.**
145 Adams Avenue
Hauppauge, New York 11788



1N4446 THRU 1N4449

SILICON SWITCHING DIODE

JEDEC DO-35 CASE

DESCRIPTION

The CENTRAL SEMICONDUCTOR 1N4446 series types are very high speed Silicon Switching Diodes designed for computer and general purpose applications.

MAXIMUM RATINGS ($T_A=25^{\circ}\text{C}$)

	SYMBOL		UNIT
Peak Repetitive Reverse Voltage	V_{RRM}	100	V
Peak Working Reverse Voltage	V_{RWM}	75	V
Average Forward Current	I_O	150	mA
Forward Steady-State Current	I_F	200	mA
Peak Forward Surge Current (1.0 μ s pulse)	I_{FSM}	2000	mA
Power Dissipation	P_D	500	mW
Operating and Storage Junction Temperature	T_J, T_{stg}	-65 TO +200	$^{\circ}\text{C}$

ELECTRICAL CHARACTERISTICS ($T_A=25^{\circ}\text{C}$ unless otherwise noted)

SYMBOL	TEST CONDITIONS	1N4446		1N4447		1N4448		1N4449		UNIT
		MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	
BV_R	$I_R=5\mu\text{A}$	75		75		75		75		V
BV_R	$I_R=100\mu\text{A}$	100		100		100		100		V
I_R	$V_R=20\text{V}$		25		25		25		25	nA
I_R	$V_R=20\text{V}, T_A=100^{\circ}\text{C}$		-		-		3.0		3.0	μA
I_R	$V_R=20\text{V}, T_A=150^{\circ}\text{C}$		50		50		50		50	μA
V_F	$I_F=5.0\text{mA}$	-	-	-	-	0.62	0.72	0.63	0.73	V
V_F	$I_F=20\text{mA}$		1.0		1.0		-		-	V
V_F	$I_F=30\text{mA}$		-		-		-		1.0	V
V_F	$I_F=100\text{mA}$		-		-		1.0		-	V
C_T	$V_R=0, f=1.0\text{ MHz}$		4.0		2.0		4.0		2.0	pF
t_{rr}	$V_R=6.0\text{V}, I_F=10\text{mA},$ $I_{rr}=1.0\text{mA}, R_L=100\Omega$		4.0		4.0		4.0		4.0	nS
$V_{FM(REC)}$	$I_F=50\text{mA}, R_L=50\Omega$		-		-		2.5		2.5	V

OUTSTANDING SUPPORT AND SUPERIOR SERVICES



PRODUCT SUPPORT

Central's operations team provides the highest level of support to insure product is delivered on-time.

- Supply management (Customer portals)
- Inventory bonding
- Consolidated shipping options
- Custom bar coding for shipments
- Custom product packing

DESIGNER SUPPORT/SERVICES

Central's applications engineering team is ready to discuss your design challenges. Just ask.

- Free quick ship samples (2nd day air)
- Online technical data and parametric search
- SPICE models
- Custom electrical curves
- Environmental regulation compliance
- Customer specific screening
- Up-screening capabilities
- Special wafer diffusions
- PbSn plating options
- Package details
- Application notes
- Application and design sample kits
- Custom product and package development

CONTACT US

Corporate Headquarters & Customer Support Team

Central Semiconductor Corp.
145 Adams Avenue
Hauppauge, NY 11788 USA
Main Tel: (631) 435-1110
Main Fax: (631) 435-1824
Support Team Fax: (631) 435-3388
www.centrasemi.com

Worldwide Field Representatives:

www.centrasemi.com/wwreps

Worldwide Distributors:

www.centrasemi.com/wwdistributors

For the latest version of Central Semiconductor's **LIMITATIONS AND DAMAGES DISCLAIMER**, which is part of Central's Standard Terms and Conditions of sale, visit: www.centrasemi.com/terms