

Excellent Integrated System Limited


Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Molex Connector Corporation](#)
[0397070004](#)

For any questions, you can email us directly:

sales@integrated-circuit.com



PART NUMBER DATA							
CIRCUITS	PART NUMBER	ENGINEERING NUMBER	COLOR	A IN mm		B IN mm	
2	397070002	M750B-06-5-02-3	GREEN	.52	13.2	.300	7.62
3	397070003	M750B-06-5-03-3	GREEN	.82	20.8	.600	15.24
4	397070004	M750B-06-5-04-3	GREEN	1.12	28.4	.900	22.86
5	397070005	M750B-06-5-05-3	GREEN	1.42	36.1	1.200	30.48
6	397070006	M750B-06-5-06-3	GREEN	1.72	43.7	1.500	38.10
7	397070007	M750B-06-5-07-3	GREEN	2.02	51.3	1.800	45.72
8	397070008	M750B-06-5-08-3	GREEN	2.32	58.9	2.100	53.34
9	397070009	M750B-06-5-09-3	GREEN	2.62	66.5	2.400	60.96
10	397070010	M750B-06-5-10-3	GREEN	2.92	74.2	2.700	68.58
11	397070011	M750B-06-5-11-3	GREEN	3.22	81.8	3.000	76.20
12	397070012	M750B-06-5-12-3	GREEN	3.52	89.4	3.300	83.82

REF. LAST 2 DIGITS OF PART NUMBER EQUALS CIRCUIT COUNT

CONTACT FACTORY FOR OPTIONAL COLORS

M750B-06-5-XX-3

COLOR

POLES

PITCH

STYLE

SERIES

SPECIFICATIONS

1. MATERIAL:

- A. SCREW: STEEL, M3, ZINC PLATED
 - B. CONTACT : BRONZE, TIN PLATED
 - C. CAGE: BRASS, NICKEL PLATED
 - D. BODY : PA66, UL94 V-0
 - E. COVER: PA66, UL94 V-0
2. WIRE SIZE: 30-12AWG
 3. RATING: 15A AT 51-150V, 15A AT 151-300V
 4. POWER-FREQUENCY WITHSTAND: AC 2500V/1MIN.
 5. INSULATION RESISTANCE: DC500V 500M Ω OR ABOVE
 6. RATED IMPULSE VOLTAGE: 4000V/MINUS AND PLUS 5 TIMES EACH
 7. WIRE STRIP LENGTH: .28 IN. (7.0mm)
 8. SCREW TORQUE: 5.0 IN LBS. (0.56 N.M)
 9. OPERATING TEMPERATURE: -40°C TO +105°C
 10. DIMS SHOWN ARE FOR REFERENCE ONLY

RELEASED EC NO. IP62014-1533 DRAWN: RSTONE CHKD: G. FARNS APPR: JFMURPHY 2014/10/16 A	I 2014/02/27 JFMURPHY 2014/10/16	QUALITY SYMBOL ▽=0 ▽=0	DESCRIPTION DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE		SCALE	DESIGN UNITS	THIRD ANGLE PROJECTION
					mm	INCH	IN/MM	---	METRIC	
				4 PLACES	±---	±---	DRAWN BY DATE	TITLE	PLUGABLE TERMINAL BLOCK 7.62MM (.300) PITCH VERTICAL, REAR FACING MOLEX INCORPORATED	
				3 PLACES	±---	±.005	CHECKED BY DATE			
				2 PLACES	±.10	±.01	G. FARNS	---		
				1 PLACE	±.03	±.01	APPROVED BY DATE			
					ANGULAR ±---	JFMURPHY 2014/10/16		DOCUMENT NO.		
							MATERIAL NO.	SEE CHART	SD-39707-001	1 OF 1
							SIZE C	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION		