

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

Molex Connector Corporation 0397080004

For any questions, you can email us directly: sales@integrated-circuit.com



Distributor of Molex Connector Corporation: Excellent Integrated System Limited Datasheet of 0397080004 - TERM PLUG HORIZ 50MM 4C GREEN

11 Contactius: sples@integrated-circuit.com Website: www.integrated-circuit.com

1.08 27.5	J
8.3 C C B	-
, X8 0W .59 15.0 WIRE ENTRY	Н
.87 22.0	c
REF. LAST 2 DIGITS OF PART NUMBER EQUALS CIRCUIT COUNT PART NUMBER DATA CIRCUITS PART NUMBER COLOR A IN mm B IN mm RIMBER 2 397080002 M753B-01-1-02-3 GREEN .42 10.6 .197 5.00	F
M753B-01-1-03-3 (6REN 6.1 15.6 .394 10.00 4 397080003 M753B-01-1-03-3 (6REN 6.1 15.6 .394 10.00 5 397080005 M753B-01-1-05-3 (GREN 8.1 26.6 .590 15.00 5 397080005 M753B-01-1-05-3 (GREN 8.1 26.6 .590 15.00 6 397080006 M753B-01-1-05-3 (GREN 1.01 25.6 .787 19.99 6 397080006 M753B-01-1-05-3 (GREN 1.02 30.6 .984 24.99 6 397080006 M753B-01-1-05-3 (GREN 1.03 30.6 .984 24.99 6 397080006 M753B-01-1-08-3 (GREN 1.04 35.6 1.574 39.99 6 397080006 M753B-01-1-08-3 (GREN 1.05 45.6 1.574 39.99 6 397080009 M753B-01-1-08-3 (GREN 1.05 45.6 1.574 39.99 6 397080009 M753B-01-1-10-3 (GREN 1.05 45.6 1.574 39.99 6 397080009 M753B-01-1-10-3 (GREN 1.05 45.6 1.574 44.99 6 397080009 M753B-01-1-11-3 (GREN 1.05 45.6 1.574 39.99 6 397080009 M753B-01-1-13-3 (GREN 1.05 45.6 1.574 39.	E
14	
1. MATERIAL: 19 M753B-01-1-19-3 [GREEN 3.76 95.6 3.542 89.98] A. BLOCK: STEEL ZINC PLATED 20 M753B-01-1-20-3 [GREEN 3.76 10.06 3.739 94.98] B. SCREW: M2.5, STEEL ZINC PLATED 21 M753B-01-1-21-3 [GREEN 4.16 105.6 3.936 99.97] C. BODY: PA66 UL94 V-0 22 M753B-01-1-22-3 [GREEN 4.35 110.6 4.133 104.97] D. CAM: STAINLESS STEEL 23 M753B-01-1-23-3 [GREEN 4.55 115.6 4.330 109.97] E. COVER: PA66 UL94 V-0 F. TERMINAL: BRASS TIN PLATED	c
2. WIRE SIZE: 30 TO 12AWG 3. RATING: 15A AT 51-150V, 15A AT 151-300V 4. MAX TORQUE: 3.5 IN. LBS. (.4 Nm) 5. WIRE STRIP: .37 (9.5mm) CONTROL FACTOR FACTOR OF HONGE COCONS GENERAL TOLERANCES DIMENSION STYLE SCALE DESIGN UNITS OF THIRD ANG (UNLESS SPECIFIED) (UNLESS SPECIFIED) METRIC GENERAL TOLERANCES DIMENSION STYLE SCALE DESIGN UNITS OF THIRD ANG (UNLESS SPECIFIED) WETCH OF THIRD ANG (UNLESS SPECIFIED) TITLE TRAINAL PLUG, 5.0MM 4 PLACES 1	LE B
6. DIELECTRIC VOLTAGE WITHSTAND: AC 2500V FOR 1 MINUTE 7. INSULATION RESISTANCE: DC 500V, 500MΩ 8. RATED IMPULSE VOLTAGE: 4000V, PLUS AND MINUS 5 TIMES EACH 9. OPERATING TEMPERATURE: -40°C TO +105°C 10. DIMS SHOWN ARE FOR REFERENCE ONLY A SPROVED BY DATE APPROVED BY DATE APPROV	= 1