

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Cinch Connectivity Solutions](#)

[ATT-0276-06-SMA-02](#)

For any questions, you can email us directly:

sales@integrated-circuit.com



NOTES:

1.0 SPECIFICATIONS:

1.1 FREQUENCY RANGE: DC to 12.4GHz

1.2 ATTENUATION VALUES: 1 THRU 30dB
IN 1dB INCREMENTS

1.3 ATTENUATION ACCURACY:

1-6dB ± 0.3 dB

7-20dB ± 0.5 dB

21-30dB ± 1.0 dB


1.4 MAXIMUM VSWR (GHz):
1.07+.015f(GHz)

1.5 MAXIMUM INPUT POWER: 2 WATTS AVG.
AT +25°C DERATED LINEARLY TO 0.5
WATTS AT +125°C

1.6 OPERATING TEMP. RANGE: -65°C to +125°C

MARKING:

2.1 MARK UNIT AS SHOWN
(REF.: INK-09012-27-XX)



ATTENUATION VALUE	DIM A
1 - 12dB	.750
13 - 30dB	.875

REV.	DESCRIPTION	DATE
1	RELEASED	8/3/91
A	EON 11574	2/18/92
B	EON 11737	4/14/92
C	EON 12138	11/4/92
CI	ADDED TITLEBLOCK	3/22/05
D	EON 21185	1/10/07

UNLESS OTHERWISE
NOTED DIMENSIONS
ARE IN INCHES AND
TOLERANCES ARE:

3 PLACE DECIMALS $\pm .005$

2 PLACE DECIMALS $\pm .02$

FRACTIONS $\pm 1/64$

PARALLELITY: T.I.R. _____

FLATNESS: T.I.R. _____

CONCENTRICITY: T.I.R. _____

ANGLES AND PERPENDICULARITY: $\pm 1^\circ$

PSCW NO.

34078

MIDWEST MICROWAVE

NOTICE: The information
contained in this
drawing is proprietary
and must not be used
without the permission
of Midwest Microwave

TITLE

ATTENUATOR

DRAWN/DATE

C.RICKARD
7/31/91

ENG./DATE

G.KOZAK
8/2/91

CHECKED/DATE

A.BEATTY
8/2/91

APPROVED/DATE

DRAWING NUMBER

ATT-0276-XX-SMA-02

SCALE:

5=1

SHEET 1 of 1