

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[QT Brightek \(QTB\)](#)
[QBLP651-IR3](#)

For any questions, you can email us directly:
sales@integrated-circuit.com

QT-Brightek Chip LED Series
1206 (with Inner Lens) IR LED
Part No.: QBLP650-IR3

Product: QBLP651-IR3	Date: May 11, 2015	Page 1 of 9
	Version# 1.0	



QBLP651-IR3

1206 LED with Inner Lens

Table of Contents:

Introduction 3

Electrical / Optical Characteristic (Ta=25 °C) 4

Absolute Maximum Rating 4

Characteristic Curves..... 5

Solder Profile & Footprint 6

Packing 7

Labeling 8

Ordering Information 8

Revision History 9

Disclaimer 9

Product: QBLP651-IR3	Date: May 11, 2015	Page 2 of 9
	Version# 1.0	



QBLP651-IR3

1206 LED with Inner Lens

Introduction

Feature:

- Water clear lens
- Package in tape and reel
- 1206 Package with Inner Lens
- AlGaAs technology
- Viewing Angle = 40 deg

Description:

These top mount bright 1206 LEDs have a height profile of 1.4mm, which is ideal in any kind of back lighting application. Also, it is a light weight model that is good for miniature products.

Application:


- Infrared Sensor
- Optoelectronic Switch
- Smoke detector
- Drive sensor

Certification & Compliance:

- TS16949
- ISO9001
- RoHS Compliant



Dimension:



Product: QBLP651-IR3	Date: May 11, 2015	Page 3 of 9
	Version# 1.0	



QBLP651-IR3

1206 LED with Inner Lens

Electrical / Optical Characteristic (Ta=25 °C)

Product	Color	I _F (mA)	V _F (V)		λ _P (nm)			I _e (mW/sr)		
			Typ.	Max.	Min.	Typ.	Max.	Min.	Typ.	Max.
QBLP651-IR1	Infrared	20	1.4	1.8	-	850	-	0.6	1.9	2.6


Absolute Maximum Rating

Material	P _d (mW)	I _F (mA)	I _{FP} (A)*	V _R (V)	T _{OP} (°C)	T _{ST} (°C)	T _{SOL} (°C)**
AlGaAs	90	50	1	5	-40 ~ +80	-40 ~ +85	260

*Duty cycle=1%, Pulse width 100us

**IR Reflow for no more than 10 sec @ 260 °C


Characteristic Curves




Product: QBLP651-IR3	Date: May 11, 2015	Page 5 of 9
	Version# 1.0	

Solder Profile & Footprint

- Recommended tin solder specifications: melting temperature in the range of 178~192 °C
- The recommended reflow soldering profile is as follows (temperatures indicated are as measured on the surface of the LED resin):



Recommended Pad Layout



Units: mm

Tolerance: ± 0.1mm

Product: QBLP651-IR3	Date: May 11, 2015	Page 6 of 9
	Version# 1.0	




QBLP651-IR3

1206 LED with Inner Lens


Packing

Reel Dimension:




Unit: mm

Tape Dimension:




Unit: mm

Arrangement of Tape:



Packaging Specification:



Product: QBLP651-IR3	Date: May 11, 2015	Page 7 of 9
	Version# 1.0	



QBLP651-IR3

1206 LED with Inner Lens

Labeling



Part No: _____

Customer P/N: _____

Item: _____

Q'ty: _____

Vf: _____

Iv: _____

WI: _____

Date: _____

Made in China

Ordering Information

Part #	Orderable Part #	Spec Range	Quantity per reel
QBLP651-IR3	QBLP651-IR3	Ie=1.9mW/sr typ. / λp=850nm typ. @ I _F =20mA	3,000 units

Product: QBLP651-IR3	Date: May 11, 2015	Page 8 of 9
	Version# 1.0	



QBLP651-IR3

1206 LED with Inner Lens

Revision History

Description:	Revision #	Revision Date
New Release of QBLP651-IR3	V1.0	05/11/2015

Disclaimer

QT-BRIGHTTEK reserves the right to make changes without further notice to any products herein to improve reliability, function or design. QT-BRIGHTTEK does not assume any liability arising out of the application or use of any product or circuit described herein; neither does it convey any license under its patent rights, nor the rights of others.

Life Support Policy

QT-BRIGHTTEK's products are not authorized for use as critical components in life support devices or systems without the express written approval of QT-BRIGHTTEK. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury of the user.
2. A critical component in any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

Product: QBLP651-IR3	Date: May 11, 2015	Page 9 of 9
	Version# 1.0	