

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Molex Connector Corporation](#)
[43020-1600](#)





For any questions, you can email us directly:

sales@integrated-circuit.com

ASSEMBLY ITEM NUMBER	PART CHARACTERISTICS		MATERIAL
	NUMBER OF POSITION	PANEL MOUNT OPTION	
43020-0200	02	YES	"B"
43020-0201	02	NO	
43020-0400	04	YES	
43020-0401	04	NO	
43020-0600	06	YES	
43020-0601	06	NO	
43020-0800	08	YES	
43020-0801	08	NO	
43020-1000	10	YES	
43020-1001	10	NO	
43020-1200	12	YES	
43020-1201	12	NO	
43020-1400	14	YES	
43020-1401	14	NO	
43020-1600	16	YES	
43020-1601	16	NO	
43020-2000	20	YES	
43020-2001	20	NO	
43020-2200	22	YES	
43020-2201	22	NO	
43020-2400	24	YES	
43020-2401	24	NO	




CKT. NO.	DIM. "A"	DIM. "B"	DIM. "C"	DIM. "D"
2	.182(3.89)	N/A	.166(4.29)	.311(7.90)
4	.270(6.89)	.118(3.00)	.284(7.20)	.429(10.90)
6	.388(9.85)	.236(6.00)	.402(10.20)	.547(13.89)
8	.506(12.85)	.354(9.00)	.520(13.20)	.665(16.89)
10	.624(15.85)	.472(12.00)	.638(16.20)	.783(19.89)
12	.742(18.85)	.591(15.00)	.756(19.20)	.901(22.89)
14	.860(21.85)	.709(18.00)	.874(22.20)	1.019(25.88)
16	.978(24.85)	.827(21.00)	.992(25.20)	1.137(28.88)
18	1.096(27.85)	.945(24.00)	1.110(28.20)	1.255(31.88)
20	1.215(30.85)	1.063(27.00)	1.229(31.20)	1.373(34.87)
22	1.333(33.85)	1.181(30.00)	1.347(34.20)	1.491(37.87)
24	1.451(36.85)	1.299(33.00)	1.465(37.20)	1.609(40.87)

- NOTES:
- HOUSING MATERIAL:
 - "A" - UNFILLED POLYESTER, RATED UL, 94V-0, COLOR IS BLACK.
 - "B" - UNFILLED NYLON, RATED UL, 94V-0, HALOGEN-FREE, COLOR IS BLACK.
 - FINISH: N/A
 - PRODUCT SPECIFICATION: PS-43045
 - PACKAGING SPECIFICATION: PK-43020-001
 - THIS HOUSING MATES WITH MICRO-FIT RECEPTACLE #43025-****
 - THIS HOUSING TO BE USED WITH MOLEX MALE TERMINAL #43031-****
 - DESIGNED FOR .055(1.4) MINIMUM TO A .100(2.54) MAXIMUM THICK PANEL OR PRINTED CIRCUIT BOARD.
 - SEE SECTION "D"-D' FOR TERMINAL ORIENTATION IN HOUSING.
 - PANEL MOUNT FEATURES MUST LOCK ON SIDE OPPOSITE PUNCH SIDE FOR OPTIMUM RETENTION.
 - PART CONFORMS TO CLASS "B" REQUIREMENTS OF COSMETIC SPECIFICATION PS-45499-002. SOME HOUSINGS MAY HAVE A SMALL GATE BLEMISH NEAR THE GATE LOCATION THAT DOES NOT AFFECT FUNCTIONALITY.




SECTION "E"-E' NO SCALE

RECOMMENDED PANEL CUT-OUT



SECTION "D"-D' WITH TERMINAL SCALE: X0



PLUG WITH OPTIONAL PANEL MOUNTS ISO VIEW (8 CIRCUIT SHOWN)

MATED MICRO-FIT CONNECTOR

QUALITY SYMBOLS	GENERAL TOLERANCES (UNLESS SPECIFIED)		DRAWN BY		DATE	TITLE	DESIGN UNITS	THIRD ANGLE PROJECTION
	mm	INCH	AFG	DATE	1993/01/07	MICRO-FIT(3.0) 2 THRU 24 CIRCUIT PLUG WITH OPTIONAL PANEL MOUNTS		
∇=0	4 PLACES	±.010	AFG	DATE	1993/01/07		METRIC	
∇=0	3 PLACES	±.014	BAP	DATE	1993/01/07			
∇=0	2 PLACES	±.025	AFG	DATE	1993/01/07			
∇=0	1 PLACE	±.035	AFG	DATE	1993/01/07			
∇=0	0 PLACE	±.050	AFG	DATE	1993/01/07			
ANGULAR ±1/2°			APPROVED BY		DATE			
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS			MATERIAL NO.		2010/11/18			
SEE CHART			DOCUMENT NO.		SDA-43020-****			
THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION			SHEET NO.		1 OF 1			