

## Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[STMicroelectronics](#)

[HCF4053M013TR](#)

For any questions, you can email us directly:


[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)



## HCF4053B

### TRIPLE 2-CHANNEL ANALOG MULTIPLEXER/DEMULTIPLEXER

- LOW "ON" RESISTANCE : 125Ω (Typ.) OVER 15V p.p SIGNAL-INPUT RANGE FOR  $V_{DD} - V_{EE} = 15V$
- HIGH "OFF" RESISTANCE : CHANNEL LEAKAGE  $\pm 100pA$  (Typ.) at  $V_{DD} - V_{EE} = 18V$
- BINARY ADDRESS DECODING ON CHIP
- HIGH DEGREE OF LINEARITY : < 0.5% DISTORTION TYP. at  $f_{IS} = 1KHz$ ,  $V_{IS} = 5 V_{pp}$ ,  $V_{DD} - V_{SS} \geq 10V$ ,  $R_L = 10K\Omega$
- VERY LOW QUIESCENT POWER DISSIPATION UNDER ALL DIGITAL CONTROL INPUT AND SUPPLY CONDITIONS : 0.2  $\mu W$  (Typ.) at  $V_{DD} - V_{SS} = V_{DD} - V_{EE} = 10V$
- MATCHED SWITCH CHARACTERISTICS :  $R_{ON} = 5\Omega$  (Typ.) FOR  $V_{DD} - V_{EE} = 15V$
- WIDE RANGE OF DIGITAL AND ANALOG SIGNAL LEVELS : DIGITAL 3 to 20, ANALOG TO 20V p.p.
- QUIESCENT CURRENT SPECIF. UP TO 20V
- 5V, 10V AND 15V PARAMETRIC RATINGS
- INPUT LEAKAGE CURRENT  $I_l = 100nA$  (MAX) AT  $V_{DD} = 18V$   $T_A = 25^\circ C$
- 100% TESTED FOR QUIESCENT CURRENT
- MEETS ALL REQUIREMENTS OF JEDEC JESD13B " STANDARD SPECIFICATIONS FOR DESCRIPTION OF B SERIES CMOS DEVICES"



#### ORDER CODES


| PACKAGE | TUBE       | T & R         |
|---------|------------|---------------|
| DIP     | HCF4053BEY |               |
| SOP     | HCF4053BM1 | HCF4053M013TR |

technology available in DIP and SOP packages. The HCF4053B analog multiplexer/demultiplexer is a digitally controlled analog switch having low ON impedance and very low OFF leakage current. This multiplexer circuit dissipate extremely low quiescent power over the full  $V_{DD} - V_{SS}$  and  $V_{DD} - V_{EE}$  supply voltage range, independent of the logic state of the control signals. When a logic "1" is present at the inhibit input terminal all channel are off. This device is a triple 2-channel multiplexer having three separate digital control inputs, A, B, and C, and an inhibit input. Each control input selects one of a pair of channels which are connected in a single pole double-throw configuration.

#### DESCRIPTION


The HCF4053B is a monolithic integrated circuit fabricated in Metal Oxide Semiconductor

#### PIN CONNECTION



## HCF4053B

### INPUT EQUIVALENT CIRCUIT



### PIN DESCRIPTION


| PIN No             | SYMBOL   | NAME AND FUNCTION              |
|--------------------|----------|--------------------------------|
| 11, 10, 9          | A, B, C  | Binary Control Inputs          |
| 6                  | INH      | Inhibit Inputs                 |
| 12, 13, 2, 1, 5, 3 | IN/OUT   | ax,ay,bx,by,cx,cy Input/Output |
| 14                 | OUT/IN   | ax or ay                       |
| 15                 | OUT/IN   | bx or by                       |
| 4                  | OUT/IN   | cx or cy                       |
| 7                  | $V_{EE}$ | Supply Voltage                 |
| 8                  | $V_{SS}$ | Negative Supply Voltage        |
| 16                 | $V_{DD}$ | Positive Supply Voltage        |

### TRUTH TABLE

| INHIBIT | C or B or A |                |
|---------|-------------|----------------|
| 0       | 0           | ax or bx or cx |
| 0       | 1           | ay or by or cy |
| 1       | X           | NONE           |

X : Don't Care

### FUNCTIONAL DIAGRAM



## HCF4053B

### ABSOLUTE MAXIMUM RATINGS

| Symbol    | Parameter                               | Value                  | Unit |
|-----------|-----------------------------------------|------------------------|------|
| $V_{DD}$  | Supply Voltage                          | -0.5 to +22            | V    |
| $V_I$     | DC Input Voltage                        | -0.5 to $V_{DD} + 0.5$ | V    |
| $I_I$     | DC Input Current                        | $\pm 10$               | mA   |
| $P_D$     | Power Dissipation per Package           | 500 (*)                | mW   |
|           | Power Dissipation per Output Transistor | 100                    | mW   |
| $T_{op}$  | Operating Temperature                   | -55 to +125            | °C   |
| $T_{stg}$ | Storage Temperature                     | -65 to +150            | °C   |

Absolute Maximum Ratings are those values beyond which damage to the device may occur. Functional operation under these conditions is not implied.

All voltage values are referred to  $V_{SS}$  pin voltage.

(\*) 500mW at 65 °C; derate to 300mW by 10mW/°C from 65°C to 85°C

### RECOMMENDED OPERATING CONDITIONS

| Symbol   | Parameter             | Value         | Unit |
|----------|-----------------------|---------------|------|
| $V_{DD}$ | Supply Voltage        | 3 to 20       | V    |
| $V_I$    | Input Voltage         | 0 to $V_{DD}$ | V    |
| $T_{op}$ | Operating Temperature | -55 to 125    | °C   |

## HCF4053B

### DC SPECIFICATIONS

| Symbol                            | Parameter                                                      | Test Condition                       |                                                                                                                             |                        |                        | Value                 |                   |      |             |      |              |      |    | Unit |
|-----------------------------------|----------------------------------------------------------------|--------------------------------------|-----------------------------------------------------------------------------------------------------------------------------|------------------------|------------------------|-----------------------|-------------------|------|-------------|------|--------------|------|----|------|
|                                   |                                                                | V <sub>IS</sub><br>(V)               | V <sub>EE</sub><br>(V)                                                                                                      | V <sub>SS</sub><br>(V) | V <sub>DD</sub><br>(V) | T <sub>A</sub> = 25°C |                   |      | -40 to 85°C |      | -55 to 125°C |      |    |      |
|                                   |                                                                |                                      |                                                                                                                             |                        |                        | Min.                  | Typ.              | Max. | Min.        | Max. | Min.         | Max. |    |      |
| I <sub>L</sub>                    | Quiescent Device Current (all switches ON or all switches OFF) |                                      |                                                                                                                             |                        | 5                      |                       | 0.04              | 5    |             | 150  |              | 150  | μA |      |
|                                   |                                                                |                                      |                                                                                                                             |                        | 10                     |                       | 0.04              | 10   |             | 300  |              | 300  |    |      |
|                                   |                                                                |                                      |                                                                                                                             |                        | 15                     |                       | 0.04              | 20   |             | 600  |              | 600  |    |      |
|                                   |                                                                |                                      |                                                                                                                             |                        | 20                     |                       | 0.08              | 100  |             | 3000 |              | 3000 |    |      |
| SWITCH                            |                                                                |                                      |                                                                                                                             |                        |                        |                       |                   |      |             |      |              |      |    |      |
| R <sub>ON</sub>                   | Resistance                                                     | 0 ≤ V <sub>I</sub> ≤ V <sub>DD</sub> | 0                                                                                                                           | 0                      | 5                      |                       | 470               | 1050 |             | 1200 |              | 1200 | Ω  |      |
|                                   |                                                                |                                      |                                                                                                                             |                        | 10                     |                       | 180               | 400  |             | 520  |              | 520  |    |      |
|                                   |                                                                |                                      |                                                                                                                             |                        | 15                     |                       | 125               | 280  |             | 360  |              | 360  |    |      |
| Δ <sub>ON</sub>                   | Resistance Δ <sub>RON</sub> (between any 2 of 4 switches)      | 0 ≤ V <sub>I</sub> ≤ V <sub>DD</sub> | 0                                                                                                                           | 0                      | 5                      |                       | 10                |      |             |      |              |      | Ω  |      |
|                                   |                                                                |                                      |                                                                                                                             |                        | 10                     |                       | 10                |      |             |      |              |      |    |      |
|                                   |                                                                |                                      |                                                                                                                             |                        | 15                     |                       | 5                 |      |             |      |              |      |    |      |
| OFF*                              | Channel Leakage Current (All Channel OFF) (COMMON O/I)         |                                      | 0                                                                                                                           | 0                      | 18                     |                       | ±0.1              | 100  |             | 1000 |              | 1000 | nA |      |
| OFF*                              | Channel Leakage Current (Any Channel OFF)                      |                                      | 0                                                                                                                           | 0                      | 18                     |                       | ±0.1              | 100  |             | 1000 |              | 1000 | nA |      |
| C <sub>I</sub>                    | Input Capacitance                                              |                                      | -5                                                                                                                          | -5                     | 5                      |                       | 5                 |      |             |      |              |      | pF |      |
| C <sub>O</sub>                    | Output Capacitance                                             |                                      |                                                                                                                             |                        |                        |                       | 9                 |      |             |      |              |      |    |      |
| C <sub>IO</sub>                   | Feed through                                                   |                                      |                                                                                                                             |                        |                        |                       | 0.2               |      |             |      |              |      |    |      |
| CONTROL (Address or Inhibit)      |                                                                |                                      |                                                                                                                             |                        |                        |                       |                   |      |             |      |              |      |    |      |
| V <sub>IL</sub>                   | Input Low Voltage                                              | = VDD thru 1KΩ                       | V <sub>EE</sub> = V <sub>SS</sub><br>R <sub>L</sub> = 1KΩ to V <sub>SS</sub><br>I <sub>IS</sub> < 2μA (on all OFF channels) | 5                      |                        |                       | 1.5               |      | 1.5         |      | 1.5          | V    |    |      |
|                                   |                                                                |                                      |                                                                                                                             | 10                     |                        |                       | 3                 |      | 3           |      | 3            |      |    |      |
|                                   |                                                                |                                      |                                                                                                                             | 15                     |                        |                       | 4                 |      | 4           |      | 4            |      |    |      |
| V <sub>IH</sub>                   | Input High Voltage                                             |                                      |                                                                                                                             | 5                      | 3.5                    |                       |                   | 3.5  |             | 3.5  |              |      | V  |      |
|                                   |                                                                |                                      |                                                                                                                             | 10                     | 7                      |                       |                   | 7    |             | 7    |              |      |    |      |
|                                   |                                                                |                                      |                                                                                                                             | 15                     | 11                     |                       |                   | 11   |             | 11   |              |      |    |      |
| I <sub>IH</sub> , I <sub>IL</sub> | Input Leakage Current                                          | V <sub>I</sub> = 0/18V               |                                                                                                                             |                        | 18                     |                       | ±10 <sup>-3</sup> | ±0.1 |             | ±1   |              | ±1   | μA |      |
| C <sub>I</sub>                    | Input Capacitance                                              |                                      |                                                                                                                             |                        |                        |                       | 5                 | 7.5  |             |      |              |      | pF |      |

\* Determined by minimum feasible leakage measurement for automating testing.

## HCF4053B

**DYNAMIC ELECTRICAL CHARACTERISTICS** ( $T_{amb} = 25^{\circ}\text{C}$ ,  $C_L = 50\text{pF}$ , all input square wave rise and fall time = 20 ns)


| Parameter                                                                                          | Test Condition         |                        |                         |                                                                                                      |                        |                        |                                                                 | Value |      |      | Unit    |
|----------------------------------------------------------------------------------------------------|------------------------|------------------------|-------------------------|------------------------------------------------------------------------------------------------------|------------------------|------------------------|-----------------------------------------------------------------|-------|------|------|---------|
|                                                                                                    | V <sub>EE</sub><br>(V) | R <sub>L</sub><br>(KΩ) | f <sub>I</sub><br>(KHz) | V <sub>I</sub><br>(V)                                                                                | V <sub>SS</sub><br>(V) | V <sub>DD</sub><br>(V) |                                                                 | Min.  | Typ. | Max. |         |
| Propagation Delay Time (signal input to output)                                                    |                        | 200                    |                         | V <sub>DD</sub><br> |                        | 5                      |                                                                 |       | 30   | 60   | ns      |
|                                                                                                    |                        |                        |                         |                                                                                                      |                        | 10                     |                                                                 |       | 15   | 30   |         |
|                                                                                                    |                        |                        |                         |                                                                                                      |                        | 15                     |                                                                 |       | 11   | 20   |         |
| Frequency Response Channel "ON" (sine wave input) at 20 log V <sub>O</sub> /V <sub>I</sub> = - 3dB | = V <sub>SS</sub>      | 1                      |                         | 5(*)                                                                                                 |                        | 10                     | V <sub>O</sub> at Common OUT/IN                                 |       | 25   |      | MHz     |
|                                                                                                    |                        |                        |                         |                                                                                                      |                        |                        | V <sub>O</sub> at any channel                                   |       | 60   |      |         |
| Feed through (all channels OFF) at 20 log V <sub>O</sub> /V <sub>I</sub> = - 40dB                  | = V <sub>SS</sub>      | 1                      |                         | 5(*)                                                                                                 |                        | 10                     | V <sub>O</sub> at Common OUT/IN                                 |       | 10   |      | MHz     |
|                                                                                                    |                        |                        |                         |                                                                                                      |                        |                        | V <sub>O</sub> at any channel                                   |       | 8    |      |         |
| Frequency Signal Crosstalk at 20 log V <sub>O</sub> /V <sub>I</sub> = -40dB                        | = V <sub>SS</sub>      | 1                      |                         | 5(*)                                                                                                 |                        | 10                     | Between any 2 Sections (IN pin 2, OUT pin 14)                   |       | 2.5  |      | MHz     |
|                                                                                                    |                        |                        |                         |                                                                                                      |                        |                        | Between any 2 Sections (IN pin 15, OUT pin 14)                  |       | 6    |      |         |
| Sine Wave Distortion f <sub>IS</sub> = 1KHz Sine Wave                                              | = V <sub>SS</sub>      | 10                     | 1                       | 2(*)                                                                                                 |                        | 5                      |                                                                 |       | 0.3  |      | %       |
|                                                                                                    |                        |                        |                         | 3(*)                                                                                                 |                        | 10                     |                                                                 |       | 0.2  |      |         |
|                                                                                                    |                        |                        |                         | 5(*)                                                                                                 |                        | 15                     |                                                                 |       | 0.12 |      |         |
| CONTROL (Address or Inhibit)                                                                       |                        |                        |                         |                                                                                                      |                        |                        |                                                                 |       |      |      |         |
| Propagation Delay: Address to Signal OUT (Channels ON or OFF)                                      | 0                      |                        |                         |                                                                                                      | 0                      | 5                      |                                                                 |       | 360  | 720  | ns      |
|                                                                                                    | 0                      |                        |                         |                                                                                                      | 0                      | 10                     |                                                                 |       | 160  | 320  |         |
|                                                                                                    | 0                      |                        |                         |                                                                                                      | 0                      | 15                     |                                                                 |       | 120  | 240  |         |
|                                                                                                    | -5                     |                        |                         |                                                                                                      | 0                      | 5                      |                                                                 |       | 225  | 450  |         |
| Propagation Delay: Inhibit to Signal OUT (Channel turning ON)                                      | 0                      | 1                      |                         |                                                                                                      | 0                      | 5                      |                                                                 |       | 360  | 720  | ns      |
|                                                                                                    | 0                      |                        |                         |                                                                                                      | 0                      | 10                     |                                                                 |       | 160  | 320  |         |
|                                                                                                    | 0                      |                        |                         |                                                                                                      | 0                      | 15                     |                                                                 |       | 120  | 240  |         |
|                                                                                                    | -10                    |                        |                         |                                                                                                      | 0                      | 5                      |                                                                 |       | 200  | 400  |         |
| Propagation Delay: Inhibit to Signal OUT (Channel turning OFF)                                     | 0                      | 10                     |                         |                                                                                                      |                        | 5                      |                                                                 |       | 200  | 450  | ns      |
|                                                                                                    | 0                      |                        |                         |                                                                                                      |                        | 10                     |                                                                 |       | 90   | 210  |         |
|                                                                                                    | 0                      |                        |                         |                                                                                                      |                        | 15                     |                                                                 |       | 70   | 160  |         |
|                                                                                                    | -10                    |                        |                         |                                                                                                      |                        | 5                      |                                                                 |       | 130  | 300  |         |
| Address or Inhibit to Signal Crosstalk                                                             | 0                      | 10 <sup>(1)</sup>      |                         |                                                                                                      | 0                      | 10                     | V <sub>C</sub> = V <sub>DD</sub> -V <sub>SS</sub> (square wave) |       | 65   |      | mV peak |

(1) Both ends of channel.

\* Peak to Peak voltage symmetrical about  $(V_{DD} - V_{EE}) / 2$

## HCF4053B

### TYPICAL BIAS VOLTAGES




The ADDRESS (digital-control inputs) and INHIBIT logic levels are : "0"= $V_{SS}$  and "1"= $V_{DD}$ . The analog signal (through the TG) may swing from  $V_{EE}$  to  $V_{DD}$

### SPECIAL CONSIDERATIONS

Control of analog signals up to 20V peak to peak can be achieved by digital signal amplitudes of 4.5 to 20V (if  $V_{DD} - V_{SS} = 3V$ , a  $V_{DD} - V_{EE}$  of up to 13V can be controlled; for  $V_{DD} - V_{EE}$  level differences above 13V, a  $V_{DD} - V_{SS}$  of at least 4.5V is required. For example, if  $V_{DD} = +5$ ,  $V_{SS} = 0$ , and  $V_{EE} = -13.5$ , analog signals from -13.5V to 4.5V can be controlled by digital inputs of 0 to 4.5V. In

certain applications, the external load resistor current may include both  $V_{DD}$  and signal-line components. To avoid drawing  $V_{DD}$  current when switch current flows into the transmission gate inputs, the voltage drop across the bidirectional switch must not exceed 0.8V (calculated from  $R_{ON}$  values shown in DC SPECIFICATIONS). No  $V_{DD}$  current will flow through  $R_L$  if the switch current flows into leads 4, 14 and 15.


### TEST CIRCUIT




$C_L$  = 50pF or equivalent (includes jig and probe capacitance)  
 $R_L$  = 200K $\Omega$   
 $R_T$  =  $Z_{OUT}$  of pulse generator (typically 50 $\Omega$ )

## HCF4053B

**WAVEFORM 1 : CHANNEL BEING TURNED ON** ( $R_L = 1K\Omega$ ,  $f=1MHz$ ; 50% duty cycle)




**WAVEFORM 2 : CHANNEL BEING TURNED OFF** ( $R_L = 1K\Omega$ ,  $f=1MHz$ ; 50% duty cycle)



## HCF4053B

### Plastic DIP-16 (0.25) MECHANICAL DATA


| DIM. | mm.  |       |      | inch  |       |       |
|------|------|-------|------|-------|-------|-------|
|      | MIN. | TYP   | MAX. | MIN.  | TYP.  | MAX.  |
| a1   | 0.51 |       |      | 0.020 |       |       |
| B    | 0.77 |       | 1.65 | 0.030 |       | 0.065 |
| b    |      | 0.5   |      |       | 0.020 |       |
| b1   |      | 0.25  |      |       | 0.010 |       |
| D    |      |       | 20   |       |       | 0.787 |
| E    |      | 8.5   |      |       | 0.335 |       |
| e    |      | 2.54  |      |       | 0.100 |       |
| e3   |      | 17.78 |      |       | 0.700 |       |
| F    |      |       | 7.1  |       |       | 0.280 |
| I    |      |       | 5.1  |       |       | 0.201 |
| L    |      | 3.3   |      |       | 0.130 |       |
| Z    |      |       | 1.27 |       |       | 0.050 |



**HCF4053B**

**SO-16 MECHANICAL DATA**

| DIM. | mm.        |      |      | inch  |       |       |
|------|------------|------|------|-------|-------|-------|
|      | MIN.       | TYP  | MAX. | MIN.  | TYP.  | MAX.  |
| A    |            |      | 1.75 |       |       | 0.068 |
| a1   | 0.1        |      | 0.2  | 0.003 |       | 0.007 |
| a2   |            |      | 1.65 |       |       | 0.064 |
| b    | 0.35       |      | 0.46 | 0.013 |       | 0.018 |
| b1   | 0.19       |      | 0.25 | 0.007 |       | 0.010 |
| C    |            | 0.5  |      |       | 0.019 |       |
| c1   | 45° (typ.) |      |      |       |       |       |
| D    | 9.8        |      | 10   | 0.385 |       | 0.393 |
| E    | 5.8        |      | 6.2  | 0.228 |       | 0.244 |
| e    |            | 1.27 |      |       | 0.050 |       |
| e3   |            | 8.89 |      |       | 0.350 |       |
| F    | 3.8        |      | 4.0  | 0.149 |       | 0.157 |
| G    | 4.6        |      | 5.3  | 0.181 |       | 0.208 |
| L    | 0.5        |      | 1.27 | 0.019 |       | 0.050 |
| M    |            |      | 0.62 |       |       | 0.024 |
| S    | 8° (max.)  |      |      |       |       |       |



## HCF4053B

---

Information furnished is believed to be accurate and reliable. However, STMicroelectronics assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of STMicroelectronics. Specifications mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information previously supplied. STMicroelectronics products are not authorized for use as critical components in life support devices or systems without express written approval of STMicroelectronics.

© The ST logo is a registered trademark of STMicroelectronics

© 2002 STMicroelectronics - Printed in Italy - All Rights Reserved  
STMicroelectronics GROUP OF COMPANIES

Australia - Brazil - Canada - China - Finland - France - Germany - Hong Kong - India - Israel - Italy - Japan - Malaysia - Malta - Morocco  
Singapore - Spain - Sweden - Switzerland - United Kingdom - United States.

© <http://www.st.com>