

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Infineon Technologies](#)
[SPP15P10P](#)

For any questions, you can email us directly:

sales@integrated-circuit.com



SPP15P10P G

SIPMOS® Small-Signal-Transistor



Feature

- P-Channel
- Enhancement mode
- Avalanche rated
- dv/dt rated
- Pb-free lead plating; RoHS compliant

Product Summary

V_{DS}	-100	V
$R_{DS(on)}$	0.24	Ω
I_D	-15	A

PG-TO220-3-1



Type	Package	Marking
SPP15P10P	PG-TO220-3-1	15P10P

Maximum Ratings, at $T_j = 25^\circ\text{C}$, unless otherwise specified

Parameter	Symbol	Value	Unit
Continuous drain current	I_D	-15	A
$T_C=25^\circ\text{C}$		-10.6	
$T_C=100^\circ\text{C}$			
Pulsed drain current	$I_{D \text{ puls}}$	-60	
$T_C=25^\circ\text{C}$			
Avalanche energy, single pulse	E_{AS}	230	mJ
$I_D=-15 \text{ A}$, $V_{DD}=-25\text{V}$, $R_{GS}=25\Omega$			
Reverse diode dv/dt	dv/dt	6	kV/ μs
$I_S=-15\text{A}$, $V_{DS}=-48\text{V}$, $di/dt=-200\text{A}/\mu\text{s}$, $T_{jmax}=150^\circ\text{C}$			
Gate source voltage	V_{GS}	± 20	V
Power dissipation	P_{tot}	128	W
$T_C=25^\circ\text{C}$			
Operating and storage temperature	T_j, T_{stg}	-55... +175	$^\circ\text{C}$
IEC climatic category; DIN IEC 68-1		55/175/56	



SPP15P10P G

Thermal Characteristics

Parameter	Symbol	Values			Unit
		min.	typ.	max.	

Characteristics

Thermal resistance, junction - case	R_{thJC}	-	-	1.17	K/W
SMD version, device on PCB:	R_{thJA}				
@ min. footprint		-	-	75	
@ 6 cm ² cooling area ¹⁾		-	-	45	

Electrical Characteristics, at $T_j = 25^\circ\text{C}$, unless otherwise specified

Parameter	Symbol	Values			Unit
		min.	typ.	max.	

Static Characteristics

Drain-source breakdown voltage $V_{GS}=0, I_D=-250\mu\text{A}$	$V_{(BR)DSS}$	-100	-	-	V
Gate threshold voltage, $V_{GS} = V_{DS}$ $I_D=-1.54\text{mA}$	$V_{GS(th)}$	-4	-3	-2.1	
Zero gate voltage drain current $V_{DS}=-100\text{V}, V_{GS}=0, T_j=25^\circ\text{C}$ $V_{DS}=-100\text{V}, V_{GS}=0, T_j=150^\circ\text{C}$	I_{DSS}	-	-0.1 -10	-1 -100	μA
Gate-source leakage current $V_{GS}=-20\text{V}, V_{DS}=0$	I_{GSS}	-	-10	-100	
Drain-source on-state resistance $V_{GS}=-10\text{V}, I_D=-10.6\text{A}$	$R_{DS(on)}$	-	0.18	0.24	Ω

¹⁾Device on 40mm*40mm*1.5mm epoxy PCB FR4 with 6cm² (one layer, 70 μm thick) copper area for drain connection. PCB is vertical without blown air.



SPP15P10P G

Electrical Characteristics, at $T_j = 25\text{ }^{\circ}\text{C}$, unless otherwise specified

Parameter	Symbol	Conditions	Values			Unit
			min.	typ.	max.	

Dynamic Characteristics

Transconductance	g_{fs}	$ V_{DS} \geq 2 \cdot I_D \cdot R_{DS(on)max}$ $I_D = -10.7\text{A}$	4.7	9.3	-	S
Input capacitance	C_{iss}	$V_{GS} = 0, V_{DS} = -25\text{V},$ $f = 1\text{MHz}$	-	944	1180	pF
Output capacitance	C_{oss}		-	226	283	
Reverse transfer capacitance	C_{rss}		-	91	114	
Turn-on delay time	$t_{d(on)}$	$V_{DD} = -50\text{V}, V_{GS} = -10\text{V},$ $I_D = -15\text{A}, R_G = 6\Omega$	-	8.9	13.4	ns
Rise time	t_r		-	30	45	
Turn-off delay time	$t_{d(off)}$		-	35	53	
Fall time	t_f		-	22	33	

Gate Charge Characteristics

Gate to source charge	Q_{gs}	$V_{DD} = -80\text{V}, I_D = -15\text{A}$	-	-4.5	-6.7	nC
Gate to drain charge	Q_{gd}		-	-15.3	-23	
Gate charge total	Q_g	$V_{DD} = -80\text{V}, I_D = -15\text{A},$ $V_{GS} = 0 \text{ to } -10\text{V}$	-	-33.4	-50	
Gate plateau voltage	$V_{(plateau)}$	$V_{DD} = -80\text{V}, I_D = -15\text{A}$	-	-5.7	-	V

Reverse Diode


Inverse diode continuous forward current	I_S	$T_A = 25^{\circ}\text{C}$	-	-	-15	A
Inv. diode direct current, pulsed	I_{SM}		-	-	-60	
Inverse diode forward voltage	V_{SD}	$V_{GS} = 0, I_F = I_S $	-	-0.94	-1.35	V
Reverse recovery time	t_{rr}	$V_R = -50\text{V}, I_F = I_S ,$ $di_F/dt = 100\text{A}/\mu\text{s}$	-	100	150	ns
Reverse recovery charge	Q_{rr}		-	419	628	nC



SPP15P10P G

1 Power dissipation


$$P_{\text{tot}} = f(T_C)$$



2 Drain current

$$I_D = f(T_C)$$


parameter: $|V_{GS}| \geq 10V$



3 Safe operating area

$$I_D = f(V_{DS})$$


parameter: $D = 0$, $T_C = 25^\circ\text{C}$



4 Max. transient thermal impedance

$$Z_{\text{thJC}} = f(t_p)$$

parameter: $D = t_p/T$






SPP15P10P G

5 Typ. output characteristic

$$I_D = f(V_{DS})$$


parameter: $T_j = 25^\circ\text{C}$, $-V_{GS}$



6 Typ. drain-source on resistance

$$R_{DS(on)} = f(I_D)$$


parameter: V_{GS} ; $T_j = 25^\circ\text{C}$, $-V_{GS}$



7 Typ. transfer characteristics

$$I_D = f(V_{GS}); |V_{DS}| \geq 2 \times |I_D| \times R_{DS(on)max}$$


parameter: $T_j = 25^\circ\text{C}$



8 Typ. forward transconductance

$$g_{fs} = f(I_D)$$

parameter: $T_j = 25^\circ\text{C}$






SPP15P10P G

9 Drain-source on-state resistance

$$R_{DS(on)} = f(T_j)$$


parameter: $I_D = -10.6 \text{ A}$, $V_{GS} = -10 \text{ V}$



10 Typ. gate threshold voltage

$$V_{GS(th)} = f(T_j)$$


parameter: $V_{GS} = V_{DS}$



11 Typ. capacitances

$$C = f(V_{DS})$$


parameter: $V_{GS}=0$, $f=1 \text{ MHz}$, $T_j = 25^\circ \text{C}$



12 Forward character. of reverse diode

$$I_F = f(V_{SD})$$

parameter: T_j






SPP15P10P G

13 Typ. avalanche energy

$E_{AS} = f(T_j)$; par.: $I_D = -15\text{ A}$,


$V_{DD} = -25\text{ V}$, $R_{GS} = 25\ \Omega$



14 Typ. gate charge


$V_{GS} = f(Q_{Gate})$

parameter: $I_D = -15\text{ A}$ pulsed, $T_j = 25^\circ\text{C}$



15 Drain-source breakdown voltage

$V_{(BR)DSS} = f(T_j)$





SPP15P10P G

Published by
Infineon Technologies AG,
Bereichs Kommunikation
St.-Martin-Strasse 53,
D-81541 München
© Infineon Technologies AG 1999
All Rights Reserved.

Attention please!

The information herein is given to describe certain components and shall not be considered as warranted characteristics.

Terms of delivery and rights to technical change reserved.

We hereby disclaim any and all warranties, including but not limited to warranties of non-infringement, regarding circuits, descriptions and charts stated herein.

Infineon Technologies is an approved CECC manufacturer.

Information

For further information on technology, delivery terms and conditions and prices please contact your nearest Infineon Technologies Office in Germany or our Infineon Technologies Representatives worldwide (see address list).

Warnings

Due to technical requirements components may contain dangerous substances.

For information on the types in question please contact your nearest Infineon Technologies Office.

Infineon Technologies Components may only be used in life-support devices or systems with the express written approval of Infineon Technologies, if a failure of such components can reasonably be expected to cause the failure of that life-support device or system, or to affect the safety or effectiveness of that device or system. Life support devices or systems are intended to be implanted in the human body, or to support and/or maintain and sustain and/or protect human life. If they fail, it is reasonable to assume that the health of the user or other persons may be endangered.