

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Schurter](#)
[0034.9857](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

FUSES

Non resettable fuses

Fuse kits

with subminiature fuses
– with wire leads
– for surface mounting and
with fuseholders

Order No.	Content							
		Types	Pieces	Rated current I _n Rated voltage U _n		Characteristic	Technical data see page	
0034.9875	 with wire leads 	Microfuses	10	100	mA	125 V	quick-acting F	72
			10	125	mA			72
			10	200	mA			72
			10	250	mA			72
			10	315	mA			72
			10	400	mA			72
			10	500	mA			72
			10	630	mA			72
			10	800	mA			72
			10	1	A			72
			10	1,25	A			72
			10	1,6	A			72
			10	2	A			72
			10	3,15	A			72
			10	4	A			72
			10	5	A			72
		Fuseholder	10	5	A	178		
		0034.9876	 with wire leads 	Microfuses MST 250	10	63	mA	250 V
10	80				mA	72		
10	160				mA	72		
10	315				mA	72		
10	500				mA	72		
10	1				A	72		
10	1,25				A	72		
10	2				A	72		
Microfuses MSF 250	10			3,15	A	250 V	quick-acting F	72
	10			50	mA			72
	10			80	mA			72
	10			315	mA			72
	10			500	mA			72
	10			1	A			72
Fuseholder	10			2	A			72
	10			3,15	A			72
	10			5	A			72
	10			5	A			180
FMS								
0034.9877	   for surface mounting	OMF 63 OMF 125	15	100	mA	OMF 63: 63 V	quick-acting F	60
			15	250	mA			60
			15	630	mA			60
			15	1	A			60
			15	1,6	A			60
			15	2	A			60
			15	3,5	A			60
		Fuseholder	15	5	A	OMF 125: 125 V		60
			10	5	A			182
		OMH 125* OMF 250	10	500	mA	250 V	quick-acting F	60
			10	800	mA			60
			10	1	A			60
			10	1,25	A			60
			10	1,6	A			60
			10	2	A			60
			10	3,15	A			60
			10	4	A			60

* suitable for OMF 63 and OMF 125

FUSES

Non resettable fuses

Fuse kits

with miniature fuses
5 x 20 mm



Order No.	Content							
		Types	Pieces	Rated current I _n Rated voltage U _n		Characteristic	Breaking capacity	Technical data see page
0034.9856		FSF 5 × 20 I _n 0,1–10 A	15	100	250 V	FSF: quick-acting F	low-breaking capacity	89, 90
			15	160				89, 90
			15	200				89, 90
			15	250				89, 90
			15	315				89, 90
0034.9857		FST 5 × 20 I _n 0,1–10 A	15	400	250 V	FST: time-lag T		89, 90
			15	500				89, 90
			15	630				89, 90
			15	800				89, 90
			15	1				89, 90
			15	1,25				89, 90
			15	1,6				89, 90
			15	2				89, 90
			15	2,5				89, 90
			15	4				89, 90
			15	5				89, 90
			15	6,3				89, 90
			15	10				89, 90
0034.9858		SP 5 × 20	15	1	250 V	quick-acting F	high-breaking capacity	96
			30	3,15				96
			30	6,3				96
			30	10				96
		FST 5 × 20	15	500	250 V	time-lag T	low-breaking capacity	90
			15	1				90
			15	1,25				90
			15	1,6				90
			15	2				90
			15	2,5				90
			15	3,15				90
			15	6,3				90
	0034.9871		SP 5 × 20	10	800	250 V	quick-acting F	high-breaking capacity
10				1	96			
10				1,6	96			
10				2	96			
10				2,5	96			
10				3,15	96			
10				5	96			
10				6,3	96			
		SPT 5 × 20	10	10	250 V	time-lag T	96	
			10	800			97	
			10	1			97	
			10	1,6			97	
			10	2			97	
	10	2,5	97					
	10	3,15	97					
	10	5	97					
	10	6,3	97					
	10	10	97					


FUSES

Non resettable fuses

Fuse kits

with subminiature fuses
– with wire leads
– for surface mounting and
with fuseholders



Order No.	Content							
		Types	Pieces	Rated current I _n Rated voltage U _n		Characteristic	Breaking capacity	Technical data see page
7189.0013		172876	50	125	125 V	quick-acting F	300 A / 125 V	55
			50	250				55
			50	375				55
			50	500				55
			50	750				55
			50	1				55
			50	1,5				55
			50	2				55
			50	2,5				55
			50	3				55
			50	3,5				55
			50	4				55
			50	5				55
			50	7				55
		231786	50			Fuseholder		177
		231787	50					
7189.0014		172322	10	63	125 V	quick-acting F	300 A / 125 V (300 A / 32 V)	83
			10	125				83
			10	250				83
			10	375				83
			10	500				83
			10	750				83
			10	1				83
			10	1,5				83
			10	2				83
			10	2,5				83
			10	3				83
			10	3,5				83
			10	4				83
			10	5				83
			10	7				83
			10	10				83
			10	12	32 V			83
			10	15				83